

Package ‘Catastro’

May 27, 2022

Type Package

Title Interface to the API 'Sede Electronica Del Catastro'

Version 0.2.2

Description Access public spatial data available under the 'INSPIRE' directive. Tools for downloading references and addresses of properties, as well as map images.

License GPL-2

URL <https://ropenspain.github.io/Catastro/>,
<https://github.com/rOpenSpain/Catastro>

BugReports <https://github.com/rOpenSpain/Catastro/issues>

Depends R (>= 3.6)

Imports dplyr, httr, mapSpain (>= 0.6.0), rappdirs (>= 0.3.0), sf (>= 1.0.0), stringi, terra, tibble, xml2

Suggests ggplot2, knitr, png, rmarkdown, slippymath, testthat (>= 3.0.0), tidyterra

VignetteBuilder knitr

Config/testthat/edition 3

Config/testthat/parallel true

Copyright © Dirección General del Catastro
<<https://www.catastro.meh.es/>>

Encoding UTF-8

LazyData true

RoxygenNote 7.2.0

NeedsCompilation no

Author Ángel Delgado Panadero [aut, cph]
(<<https://orcid.org/0000-0002-8189-9251>>),
Iñaki Ucar [ctb] (<<https://orcid.org/0000-0001-6403-5550>>),
Diego Hernangómez [aut, cre] (<<https://orcid.org/0000-0001-8457-4658>>)

Maintainer Diego Hernangómez <diego.hernangomezherrero@gmail.com>

Repository CRAN

Date/Publication 2022-05-27 08:40:19 UTC

R topics documented:

catr_atom_get_address	2
catr_atom_get_address_db_all	4
catr_atom_get_buildings	6
catr_atom_get_buildings_db_all	7
catr_atom_get_parcel	9
catr_atom_get_parcel_db_all	11
catr_atom_search_munic	13
catr_clear_cache	14
catr_get_code_from_coords	15
catr_ovc_get_cod_munic	16
catr_ovc_get_cod_provinces	17
catr_ovc_get_cpmrc	18
catr_ovc_get_reccoor	20
catr_ovc_get_reccoor_distancia	21
catr_set_cache_dir	23
catr_srs_values	24
catr_wfs_get_address_bbox	25
catr_wfs_get_buildings_bbox	27
catr_wfs_get_parcel_bbox	29
catr_wms_get_layer	32
Index	35

catr_atom_get_address *ATOM INSPIRE: Download all the Addresses of a Municipality*

Description

Get the spatial data of all the addresses belonging to a single municipality using the INSPIRE ATOM service.

Usage

```
catr_atom_get_address(
  munic,
  to = NULL,
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE
)
```

Arguments

munic	Municipality to extract, It can be a part of a string or the cadastral code. See catr_atom_search_munic() for getting the cadastral codes.
to	Optional parameter for defining the Territorial Office to which munic belongs. This parameter is a helper for narrowing the search.
cache	A logical whether to do caching. Default is TRUE. See About caching section on catr_set_cache_dir() .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
cache_dir	A path to a cache directory. On missing value the function would store the cached files on a temporary dir (See base::tempdir()).
verbose	Logical, displays information. Useful for debugging, default is FALSE.

Value

A sf object.

References

[API Documentation](#)

[INSPIRE Services for Cadastral Cartography](#)

See Also

INSPIRE API functions: [catr_atom_get_address_db_all\(\)](#), [catr_atom_get_buildings_db_all\(\)](#), [catr_atom_get_buildings\(\)](#), [catr_atom_get_parcel_db_all\(\)](#), [catr_atom_get_parcel\(\)](#), [catr_wfs_get_address_bbox\(\)](#), [catr_wfs_get_buildings_bbox\(\)](#), [catr_wfs_get_parcel_bbox\(\)](#), [catr_wms_get_layer\(\)](#)

Other INSPIRE ATOM services: [catr_atom_get_address_db_all\(\)](#), [catr_atom_get_buildings_db_all\(\)](#), [catr_atom_get_buildings\(\)](#), [catr_atom_get_parcel_db_all\(\)](#), [catr_atom_get_parcel\(\)](#), [catr_atom_search_munic\(\)](#)

Other addresses: [catr_atom_get_address_db_all\(\)](#), [catr_wfs_get_address_bbox\(\)](#)

Other spatial: [catr_atom_get_buildings\(\)](#), [catr_atom_get_parcel\(\)](#), [catr_wfs_get_address_bbox\(\)](#), [catr_wfs_get_buildings_bbox\(\)](#), [catr_wfs_get_parcel_bbox\(\)](#), [catr_wms_get_layer\(\)](#)

Examples

```
s <- catr_atom_get_address("Melque",
  to = "Segovia"
)

library(ggplot2)

ggplot(s) +
  geom_sf(aes(color = specification)) +
  coord_sf(
```

```
xlim = c(376200, 376850),
ylim = c(4545000, 4546000)
) +
labs(
  title = "Addresses",
  subtitle = "Melque de Cercos, Segovia"
)
```

catr_atom_get_address_db_all

ATOM INSPIRE: Reference Database for ATOM Addresses

Description

Create a database containing the urls provided in the INSPIRE ATOM service of the Spanish Cadastre for extracting Addresses.

- `catr_atom_get_address_db_all()` provides a top-level table including information of all the territorial offices (except Basque Country and Navarre) listing the municipalities included on each office.
- `catr_atom_get_address_db_to()` provides a table for the specified territorial office including information for each of the municipalities of that office.

Usage

```
catr_atom_get_address_db_all(
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE
)
```

```
catr_atom_get_address_db_to(
  to,
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE
)
```

Arguments

- | | |
|--------------|---|
| cache | A logical whether to do caching. Default is TRUE. See About caching section on <code>catr_set_cache_dir()</code> . |
| update_cache | A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file. |

cache_dir	A path to a cache directory. On missing value the function would store the cached files on a temporary dir (See <code>base::tempdir()</code>).
verbose	Logical, displays information. Useful for debugging, default is FALSE.
to	Territorial office. It can be any type of string, the function would perform a search using <code>base::grep()</code> .

Value

A tibble with the information requested.

- `catr_atom_get_address_db_all()` provides a tibble with the following fields:
 - `territorial_office`: Territorial office, corresponding to each province of Spain except Basque Country and Navarre.
 - `url`: ATOM url for the corresponding territorial office.
 - `munic`: Name of the municipality.
 - `date`: Reference date of the data. Note that **the information of this service is updated twice a year**.
- `catr_atom_get_address_db_to()` provides a tibble with the following fields:
 - `munic`: Name of the municipality.
 - `url`: url for downloading information of the corresponding municipality.
 - `date`: Reference date of the data. Note that **the information of this service is updated twice a year**.

Source

<https://www.catastro.minhap.es/INSPIRE/CadastralParcels/ES.SDGC.CP.atom.xml>

See Also

INSPIRE API functions: `catr_atom_get_address()`, `catr_atom_get_buildings_db_all()`, `catr_atom_get_building`, `catr_atom_get_parcel_db_all()`, `catr_atom_get_parcel()`, `catr_wfs_get_address_bbox()`, `catr_wfs_get_buildings_bbox()`, `catr_wfs_get_parcel_bbox()`, `catr_wms_get_layer()`

Other INSPIRE ATOM services: `catr_atom_get_address()`, `catr_atom_get_buildings_db_all()`, `catr_atom_get_buildings()`, `catr_atom_get_parcel_db_all()`, `catr_atom_get_parcel()`, `catr_atom_search_munic()`

Other addresses: `catr_atom_get_address()`, `catr_wfs_get_address_bbox()`

Other databases: `catr_atom_get_buildings_db_all()`, `catr_atom_get_parcel_db_all()`, `catr_atom_search_munic`, `catr_srs_values`

Examples

```
catr_atom_get_address_db_all()
```

`catr_atom_get_buildings`*ATOM INSPIRE: Download all the Buildings of a Municipality*

Description

Get the spatial data of all the buildings belonging to a single municipality using the INSPIRE ATOM service.

Usage

```
catr_atom_get_buildings(  
    munic,  
    to = NULL,  
    what = "building",  
    cache = TRUE,  
    update_cache = FALSE,  
    cache_dir = NULL,  
    verbose = FALSE  
)
```

Arguments

<code>munic</code>	Municipality to extract, It can be a part of a string or the cadastral code. See catr_atom_search_munic() for getting the cadastral codes.
<code>to</code>	Optional parameter for defining the Territorial Office to which <code>munic</code> belongs. This parameter is a helper for narrowing the search.
<code>what</code>	Information to load. It could be "building" for buildings, "buildingpart" for parts of a building or "other" for others (swimming pools, etc.).
<code>cache</code>	A logical whether to do caching. Default is TRUE. See About caching section on catr_set_cache_dir() .
<code>update_cache</code>	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
<code>cache_dir</code>	A path to a cache directory. On missing value the function would store the cached files on a temporary dir (See base::tempdir()).
<code>verbose</code>	Logical, displays information. Useful for debugging, default is FALSE.

Value

A sf object.

References

[API Documentation](#)

[INSPIRE Services for Cadastral Cartography](#)

See Also

INSPIRE API functions: [catr_atom_get_address_db_all\(\)](#), [catr_atom_get_address\(\)](#), [catr_atom_get_buildings_db_all\(\)](#), [catr_atom_get_parcel_db_all\(\)](#), [catr_atom_get_parcel\(\)](#), [catr_wfs_get_address_bbox\(\)](#), [catr_wfs_get_buildings_bbox\(\)](#), [catr_wfs_get_parcel_bbox\(\)](#), [catr_wms_get_layer\(\)](#)

Other INSPIRE ATOM services: [catr_atom_get_address_db_all\(\)](#), [catr_atom_get_address\(\)](#), [catr_atom_get_buildings_db_all\(\)](#), [catr_atom_get_parcel_db_all\(\)](#), [catr_atom_get_parcel\(\)](#), [catr_atom_search_munic\(\)](#)

Other buildings: [catr_atom_get_buildings_db_all\(\)](#), [catr_wfs_get_buildings_bbox\(\)](#)

Other spatial: [catr_atom_get_address\(\)](#), [catr_atom_get_parcel\(\)](#), [catr_wfs_get_address_bbox\(\)](#), [catr_wfs_get_buildings_bbox\(\)](#), [catr_wfs_get_parcel_bbox\(\)](#), [catr_wms_get_layer\(\)](#)

Examples

```
s <- catr_atom_get_buildings("Nava de la Asuncion",
  to = "Segovia",
  what = "building"
)

library(ggplot2)
ggplot(s) +
  geom_sf() +
  coord_sf(
    xlim = c(374500, 375500),
    ylim = c(4556500, 4557500)
  ) +
  labs(
    title = "Buildings",
    subtitle = "Nava de la Asuncion, Segovia"
  )
)
```

catr_atom_get_buildings_db_all

ATOM INSPIRE: Reference Database for ATOM Buildings

Description

Create a database containing the urls provided in the INSPIRE ATOM service of the Spanish Cadastre for extracting buildings.

- [catr_atom_get_buildings_db_all\(\)](#) provides a top-level table including information of all the territorial offices (except Basque Country and Navarre) listing the municipalities included on each office.
- [catr_atom_get_buildings_db_to\(\)](#) provides a table for the specified territorial office including information for each of the municipalities of that office.

Usage

```
catr_atom_get_buildings_db_all(
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE
)
```

```
catr_atom_get_buildings_db_to(
  to,
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE
)
```

Arguments

cache	A logical whether to do caching. Default is TRUE. See About caching section on catr_set_cache_dir() .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
cache_dir	A path to a cache directory. On missing value the function would store the cached files on a temporary dir (See base::tempdir()).
verbose	Logical, displays information. Useful for debugging, default is FALSE.
to	Territorial office. It can be any type of string, the function would perform a search using base::grep() .

Value

A tibble with the information requested.

- `catr_atom_get_buildings_db_all()` provides a tibble with the following fields:
 - `territorial_office`: Territorial office, corresponding to each province of Spain except Basque Country and Navarre.
 - `url`: ATOM url for the corresponding territorial office.
 - `munic`: Name of the municipality.
 - `date`: Reference date of the data. Note that **the information of this service is updated twice a year**.
- `catr_atom_get_buildings_db_to()` provides a tibble with the following fields:
 - `munic`: Name of the municipality.
 - `url`: url for downloading information of the corresponding municipality.
 - `date`: Reference date of the data. Note that **the information of this service is updated twice a year**.

Source

<https://www.catastro.minhap.es/INSPIRE/CadastralParcels/ES.SDGC.CP.atom.xml>

See Also

INSPIRE API functions: [catr_atom_get_address_db_all\(\)](#), [catr_atom_get_address\(\)](#), [catr_atom_get_buildings_db_all\(\)](#), [catr_atom_get_buildings\(\)](#), [catr_atom_get_parcel_db_all\(\)](#), [catr_atom_get_parcel\(\)](#), [catr_wfs_get_address_bbox\(\)](#), [catr_wfs_get_buildings_bbox\(\)](#), [catr_wfs_get_parcel_bbox\(\)](#), [catr_wms_get_layer\(\)](#)

Other INSPIRE ATOM services: [catr_atom_get_address_db_all\(\)](#), [catr_atom_get_address\(\)](#), [catr_atom_get_buildings\(\)](#), [catr_atom_get_parcel_db_all\(\)](#), [catr_atom_get_parcel\(\)](#), [catr_atom_search_munic\(\)](#)

Other buildings: [catr_atom_get_buildings\(\)](#), [catr_wfs_get_buildings_bbox\(\)](#)

Other databases: [catr_atom_get_address_db_all\(\)](#), [catr_atom_get_parcel_db_all\(\)](#), [catr_atom_search_munic\(\)](#), [catr_srs_values](#)

Examples

```
catr_atom_get_buildings_db_all()
```

`catr_atom_get_parcel` *ATOM INSPIRE: Download all the Cadastral Parcels of a Municipality*

Description

Get the spatial data of all the cadastral parcels belonging to a single municipality using the INSPIRE ATOM service.

Usage

```
catr_atom_get_parcel(  
    munic,  
    to = NULL,  
    what = "parcel",  
    cache = TRUE,  
    update_cache = FALSE,  
    cache_dir = NULL,  
    verbose = FALSE  
)
```

Arguments

munic	Municipality to extract, It can be a part of a string or the cadastral code. See catr_atom_search_munic() for getting the cadastral codes.
to	Optional parameter for defining the Territorial Office to which munic belongs. This parameter is a helper for narrowing the search.
what	Information to load. It could be "parcel" for cadastral parcels or "zoning" for cadastral zoning.
cache	A logical whether to do caching. Default is TRUE. See About caching section on catr_set_cache_dir() .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
cache_dir	A path to a cache directory. On missing value the function would store the cached files on a temporary dir (See base::tempdir()).
verbose	Logical, displays information. Useful for debugging, default is FALSE.

Value

A sf object.

References

[API Documentation](#)

[INSPIRE Services for Cadastral Cartography](#)

See Also

INSPIRE API functions: [catr_atom_get_address_db_all\(\)](#), [catr_atom_get_address\(\)](#), [catr_atom_get_buildings_db_all\(\)](#), [catr_atom_get_buildings\(\)](#), [catr_atom_get_parcel_db_all\(\)](#), [catr_wfs_get_address_bbox\(\)](#), [catr_wfs_get_buildings_bbox\(\)](#), [catr_wfs_get_parcel_bbox\(\)](#), [catr_wms_get_layer\(\)](#)

Other INSPIRE ATOM services: [catr_atom_get_address_db_all\(\)](#), [catr_atom_get_address\(\)](#), [catr_atom_get_buildings_db_all\(\)](#), [catr_atom_get_buildings\(\)](#), [catr_atom_get_parcel_db_all\(\)](#), [catr_atom_search_munic\(\)](#)

Other parcels: [catr_atom_get_parcel_db_all\(\)](#), [catr_wfs_get_parcel_bbox\(\)](#)

Other spatial: [catr_atom_get_address\(\)](#), [catr_atom_get_buildings\(\)](#), [catr_wfs_get_address_bbox\(\)](#), [catr_wfs_get_buildings_bbox\(\)](#), [catr_wfs_get_parcel_bbox\(\)](#), [catr_wms_get_layer\(\)](#)

Examples

```
s <- catr_atom_get_parcel("Melque",
  to = "Segovia",
  what = "parcel"
)

library(ggplot2)
```

```
ggplot(s) +  
  geom_sf() +  
  labs(  
    title = "Cadastral Zoning",  
    subtitle = "Melque de Cercos, Segovia"  
  )
```

catr_atom_get_parcel_db_all

ATOM INSPIRE: Reference Database for ATOM Cadastral Parcels

Description

Create a database containing the urls provided in the INSPIRE ATOM service of the Spanish Cadastre for extracting Cadastral Parcels.

- `catr_atom_get_parcel_db_all()` provides a top-level table including information of all the territorial offices (except Basque Country and Navarre) listing the municipalities included on each office.
- `catr_atom_get_parcel_db_to()` provides a table for the specified territorial office including information for each of the municipalities of that office.

Usage

```
catr_atom_get_parcel_db_all(  
  cache = TRUE,  
  update_cache = FALSE,  
  cache_dir = NULL,  
  verbose = FALSE  
)
```

```
catr_atom_get_parcel_db_to(  
  to,  
  cache = TRUE,  
  update_cache = FALSE,  
  cache_dir = NULL,  
  verbose = FALSE  
)
```

Arguments

- | | |
|--------------|---|
| cache | A logical whether to do caching. Default is TRUE. See About caching section on <code>catr_set_cache_dir()</code> . |
| update_cache | A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file. |

cache_dir	A path to a cache directory. On missing value the function would store the cached files on a temporary dir (See <code>base::tempdir()</code>).
verbose	Logical, displays information. Useful for debugging, default is FALSE.
to	Territorial office. It can be any type of string, the function would perform a search using <code>base::grep()</code> .

Value

A tibble with the information requested.

- `catr_atom_get_parcel_db_all()` provides a tibble with the following fields:
 - `territorial_office`: Territorial office, corresponding to each province of Spain except Basque Country and Navarre.
 - `url`: ATOM url for the corresponding territorial office.
 - `munic`: Name of the municipality.
 - `date`: Reference date of the data. Note that **the information of this service is updated twice a year**.
- `catr_atom_get_parcel_db_to()` provides a tibble with the following fields:
 - `munic`: Name of the municipality.
 - `url`: url for downloading information of the corresponding municipality.
 - `date`: Reference date of the data. Note that **the information of this service is updated twice a year**.

Source

<https://www.catastro.minhap.es/INSPIRE/CadastralParcels/ES.SDGC.CP.atom.xml>

See Also

INSPIRE API functions: `catr_atom_get_address_db_all()`, `catr_atom_get_address()`, `catr_atom_get_buildings_db_all()`, `catr_atom_get_buildings()`, `catr_atom_get_parcel_db_all()`, `catr_wfs_get_address_bbox()`, `catr_wfs_get_buildings_bbox()`, `catr_wfs_get_parcel_bbox()`, `catr_wms_get_layer()`

Other INSPIRE ATOM services: `catr_atom_get_address_db_all()`, `catr_atom_get_address()`, `catr_atom_get_buildings_db_all()`, `catr_atom_get_buildings()`, `catr_atom_get_parcel_db_all()`, `catr_atom_search_munic()`

Other parcels: `catr_atom_get_parcel_db_all()`, `catr_wfs_get_parcel_bbox()`

Other databases: `catr_atom_get_address_db_all()`, `catr_atom_get_buildings_db_all()`, `catr_atom_search_munic()`, `catr_srs_values`

Examples

```
catr_atom_get_parcel_db_all()
```

`catr_atom_search_munic`*ATOM INSPIRE: Search for municipality codes*

Description

Search for a municipality (as a string, part of string or code) and get the corresponding coding as per the Cadastre.

Usage

```
catr_atom_search_munic(  
  munic,  
  to = NULL,  
  cache = TRUE,  
  update_cache = FALSE,  
  cache_dir = NULL,  
  verbose = FALSE  
)
```

Arguments

<code>munic</code>	Municipality to extract, It can be a part of a string or the cadastral code.
<code>to</code>	Optional parameter for defining the Territorial Office to which <code>munic</code> belongs. This parameter is a helper for narrowing the search.
<code>cache</code>	A logical whether to do caching. Default is TRUE. See About caching section on catr_set_cache_dir() .
<code>update_cache</code>	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
<code>cache_dir</code>	A path to a cache directory. On missing value the function would store the cached files on a temporary dir (See base::tempdir()).
<code>verbose</code>	Logical, displays information. Useful for debugging, default is FALSE.

Value

A tibble.

See Also

Other INSPIRE ATOM services: [catr_atom_get_address_db_all\(\)](#), [catr_atom_get_address\(\)](#), [catr_atom_get_buildings_db_all\(\)](#), [catr_atom_get_buildings\(\)](#), [catr_atom_get_parcel_db_all\(\)](#), [catr_atom_get_parcel\(\)](#)

Other search: [catr_get_code_from_coords\(\)](#), [catr_ovc_get_cod_munic\(\)](#), [catr_ovc_get_cod_provinces\(\)](#)

Other databases: [catr_atom_get_address_db_all\(\)](#), [catr_atom_get_buildings_db_all\(\)](#), [catr_atom_get_parcel_db_all\(\)](#), [catr_srs_values](#)

Examples

```
catr_atom_search_munic("Mad")
```

catr_clear_cache	<i>Clear your CatastRo cache dir</i>
------------------	---

Description

Use this function with caution. This function would clear your cached data and configuration, specifically:

- Deletes the **CatastRo** config directory (`rappdirs::user_config_dir("CatastRo", "R")`).
- Deletes the `cache_dir` directory.
- Deletes the values on stored on `Sys.getenv("CATASTROESP_CACHE_DIR")`.

Usage

```
catr_clear_cache(config = FALSE, cached_data = TRUE, verbose = FALSE)
```

Arguments

<code>config</code>	if TRUE, will delete the configuration folder of CatastRo .
<code>cached_data</code>	If this is set to TRUE, it will delete your <code>cache_dir</code> and all its content.
<code>verbose</code>	Logical, displays information. Useful for debugging, default is FALSE.

Details

This is an overkill function that is intended to reset your status as it you would never have installed and/or used **CatastRo**.

Value

Invisible. This function is called for its side effects.

See Also

Other cache utilities: [catr_set_cache_dir\(\)](#)

Examples

```
# Don't run this! It would modify your current state
## Not run:
catr_clear_cache(verbose = TRUE)

## End(Not run)

Sys.getenv("CATASTROESP_CACHE_DIR")
```

```
catr_get_code_from_coords
```

Get the cadastral Municipality code from coordinates

Description

This function takes as an input a pair of coordinates of a sf object and returns the corresponding municipality code for that coordinates.

See also [mapSpain::esp_get_munic_siane\(\)](#) and [catr_ovc_get_cod_munic\(\)](#).

Usage

```
catr_get_code_from_coords(x, srs, verbose = FALSE, cache_dir = NULL, ...)
```

Arguments

x	It could be: <ul style="list-style-type: none"> • A pair of coordinates c(x,y). • A sf object. See Details.
srs	SRS/CRS to use on the query. To check the admitted values check catr_srs_values , specifically the <code>wfs_service</code> column. See Details .
verbose	Logical, displays information. Useful for debugging, default is FALSE.
cache_dir	A path to a cache directory. On missing value the function would store the cached files on a temporary dir (See base::tempdir()).
...	Arguments passed on to mapSpain::esp_get_munic_siane year Release year. See Details for years available.

Details

When x is a numeric vector, make sure that the srs matches the coordinate values.

When x is a sf object, only the first value would be used. The function would extract the coordinates using `sf::st_centroid(x, of_largest_polygon = TRUE)`.

Value

A tibble with the format described in [catr_ovc_get_cod_munic\(\)](#).

See Also

`mapSpain::esp_get_munic_siane()`, `sf::st_centroid()`.

Other search: `catr_atom_search_munic()`, `catr_ovc_get_cod_munic()`, `catr_ovc_get_cod_provinces()`

Examples

```
# Use with coords
catr_get_code_from_coords(c(-16.25462, 28.46824), srs = 4326)

# Use with sf
prov <- mapSpain::esp_get_prov("Caceres")
catr_get_code_from_coords(prov)
```

`catr_ovc_get_cod_munic`

OVCCallejero: Extract the code of a municipality

Description

Implementation of the OVCCallejero service [ConsultaMunicipioCodigos](#). Return the names and codes of a municipality. Returns both the codes as per the Cadastre and as per the INE (National Statistics Institute).

Usage

```
catr_ovc_get_cod_munic(cpro, cmun = NULL, cmun_ine = NULL, verbose = FALSE)
```

Arguments

<code>cpro</code>	The code of a province, as provided by <code>catr_ovc_get_cod_provinces()</code> .
<code>cmun</code>	Code of a municipality, as recorded on the Spanish Cadastre.
<code>cmun_ine</code>	Code of a municipality, as recorded on National Statistics Institute. See INE: List of municipalities
<code>verbose</code>	Logical, displays information. Useful for debugging, default is FALSE.

Details

Parameter `cpro` is mandatory. Either `cmun` or `cmun_ine` should be provided.

On a successful query, the function returns a tibble with one row including the following columns:

- `munic`: Name of the municipality as per the Cadastre.
- `catr_to`: Cadastral territorial office code.

- catr_munic: Municipality code as recorded on the Cadastre.
- catrcode: Full Cadastral code for the municipality.
- cpro: Province code as per the INE.
- catr_munic: Municipality code as per the INE.
- catrcode: Full INE code for the municipality.
- Rest of fields: Check the API Docs on [Consulta_CPMRC](#)

Value

A tibble. See **Details**

References

[ConsultaMunicipioCodigos](#)

See Also

[mapSpain::esp_get_munic\(\)](#) to get shapes of municipalities, including the INE code.

OVCCoordenadas API: [catr_ovc_get_cod_provinces\(\)](#)

Other search: [catr_atom_search_munic\(\)](#), [catr_get_code_from_coords\(\)](#), [catr_ovc_get_cod_provinces\(\)](#)

Examples

```
# Get municipality by cadastral code
ab <- catr_ovc_get_cod_munic(2, 900)

ab

# Same query using the INE code
ab2 <- catr_ovc_get_cod_munic(2, cmun_ine = 3)

ab2
```

catr_ovc_get_cod_provinces

OVCCallejero: Extract a list of provinces with their codes

Description

Implementation of the OVCCallejero service [ConsultaProvincia](#). Return a list of the provinces included on the Spanish Cadastre.

Usage

```
catr_ovc_get_cod_provinces(verbose = FALSE)
```

Arguments

verbose Logical, displays information. Useful for debugging, default is FALSE.

Value

A tibble.

References

[ConsultaProvincia](#)

See Also

OVCCoordenadas API: [catr_ovc_get_cod_munic\(\)](#)

Other search: [catr_atom_search_munic\(\)](#), [catr_get_code_from_coords\(\)](#), [catr_ovc_get_cod_munic\(\)](#)

Examples

```
catr_ovc_get_cod_provinces()
```

catr_ovc_get_cpmrc *OVCCoordenadas: Geocode a cadastral reference*

Description

Implementation of the OVCCoordenadas service [Consulta_CPMRC](#). Return the coordinates for a specific cadastral reference.

Usage

```
catr_ovc_get_cpmrc(  
  rc,  
  srs = 4326,  
  province = NULL,  
  municipality = NULL,  
  verbose = FALSE  
)
```

Arguments

rc	The cadastral reference to be geocoded.
srs	SRS/CRS to use on the query. To check the admitted values check catr_srs_values , specifically the ovc_service column.
province, municipality	Optional, used for narrowing the search.
verbose	Logical, displays information. Useful for debugging, default is FALSE.

Details

When the API does not provide any result, the function returns a tibble with the input parameters only.

On a successful query, the function returns a tibble with one row by cadastral reference, including the following columns:

- xcoord, ycoord: X and Y coordinates in the specified SRS.
- refcat: Cadastral Reference.
- address: Address as it is recorded on the Cadastre.
- Rest of fields: Check the API Docs on [Consulta_CPMRC](#)

Value

A tibble. See **Details**

References

[Consulta_CPMRC](#)

See Also

[catr_srs_values](#), `vignette("ovcservice")`

OVCCoordenadas API: `catr_ovc_get_rccoor_distancia()`, `catr_ovc_get_rccoor()`, `catr_srs_values`

Other cadastral references: `catr_ovc_get_rccoor_distancia()`, `catr_ovc_get_rccoor()`

Examples

```
# using all the arguments
catr_ovc_get_cpmrc("13077A01800039",
  4230,
  province = "CIUDAD REAL",
  municipality = "SANTA CRUZ DE MUDELA"
)

# only the cadastral reference
catr_ovc_get_cpmrc("9872023VH5797S")
```

catr_ovc_get_rccoor *OVCCoordenadas: Reverse geocode a cadastral reference*

Description

Implementation of the OVCCoordenadas service [Consulta_RCCOOR](#). Return the cadastral reference found of a set of specific coordinates.

Usage

```
catr_ovc_get_rccoor(lat, lon, srs = 4326, verbose = FALSE)
```

Arguments

lat	Latitude to use on the query. It should be specified in the same in the CRS/SRS specified by srs.
lon	Longitude to use on the query. It should be specified in the same in the CRS/SRS specified by srs.
srs	SRS/CRS to use on the query. To check the admitted values check catr_srs_values , specifically the ovc_service column.
verbose	Logical, displays information. Useful for debugging, default is FALSE.

Details

When the API does not provide any result, the function returns a tibble with the input parameters only.

On a successful query, the function returns a tibble with one row by cadastral reference, including the following columns:

- geo.xcen, geo.ycen, geo.srs: Input parameters of the query.
- refcat: Cadastral Reference.
- address: Address as it is recorded on the Cadastre.
- Rest of fields: Check the API Docs on [Consulta_RCCOOR](#)

Value

A tibble. See **Details**

References

[Consulta_RCCOOR](#)

See Also

[catr_srs_values](#), `vignette("ovcservice")`

OVCCoordenadas API: `catr_ovc_get_cpmrc()`, `catr_ovc_get_rccoor_distancia()`, `catr_srs_values`

Other cadastral references: `catr_ovc_get_cpmrc()`, `catr_ovc_get_rccoor_distancia()`

Examples

```
catr_ovc_get_rccoor(  
  lat = 38.6196566583596,  
  lon = -3.45624183836806,  
  srs = 4326  
)
```

`catr_ovc_get_rccoor_distancia`

OVCCoordenadas: Reverse geocode cadastral references on a region

Description

Implementation of the OVCCoordenadas service [Consulta_RCCOOR_Distancia](#). Return the cadastral reference found on a set of coordinates. If no cadastral references are found, the API returns a list of the cadastral references found on an area of 50 square meters around the requested coordinates.

Usage

```
catr_ovc_get_rccoor_distancia(lat, lon, srs = 4326, verbose = FALSE)
```

Arguments

<code>lat</code>	Latitude to use on the query. It should be specified in the same in the CRS/SRS specified by <code>srs</code> .
<code>lon</code>	Longitude to use on the query. It should be specified in the same in the CRS/SRS specified by <code>srs</code> .
<code>srs</code>	SRS/CRS to use on the query. To check the admitted values check catr_srs_values , specifically the <code>ovc_service</code> column.
<code>verbose</code>	Logical, displays information. Useful for debugging, default is FALSE.

Details

When the API does not provide any result, the function returns a tibble with the input parameters only.

On a successful query, the function returns a tibble with one row by cadastral reference, including the following columns:

- `geo.xcen`, `geo.ycen`, `geo.srs`: Input parameters of the query.
- `refcat`: Cadastral Reference.
- `address`: Address as it is recorded on the Cadastre.
- `cmun_ine`: Municipality Code as registered on the INE (National Statistics Institute).
- Rest of fields: Check the API Docs on [Consulta_RCCOOR_Distancia](#)

Value

A tibble. See **Details**

References

[Consulta_RCCOOR_Distancia](#)

See Also

[catr_srs_values](#), `vignette("ovcservice")`

OVCCoordenadas API: `catr_ovc_get_cpmrc()`, `catr_ovc_get_rccoor()`, `catr_srs_values`

Other cadastral references: `catr_ovc_get_cpmrc()`, `catr_ovc_get_rccoor()`

Examples

```
catr_ovc_get_rccoor_distancia(  
  lat = 40.963200,  
  lon = -5.671420,  
  srs = 4326  
)
```

catr_set_cache_dir *Set your **CatastRo** cache dir*

Description

This function will store your `cache_dir` path on your local machine and would load it for future sessions. Type `Sys.getenv("CATASTROESP_CACHE_DIR")` to find your cached path.

Alternatively, you can store the `cache_dir` manually with the following options:

- Run `Sys.setenv(CATASTROESP_CACHE_DIR = "cache_dir")`. You would need to run this command on each session (Similar to `install = FALSE`).
- Write this line on your `.Renviro`n file: `CATASTROESP_CACHE_DIR = "value_for_cache_dir"` (same behavior than `install = TRUE`). This would store your `cache_dir` permanently.

Usage

```
catr_set_cache_dir(
  cache_dir,
  overwrite = FALSE,
  install = FALSE,
  verbose = TRUE
)
```

Arguments

<code>cache_dir</code>	A path to a cache directory. On missing value the function would store the cached files on a temporary dir (See <code>base::tempdir()</code>).
<code>overwrite</code>	If this is set to <code>TRUE</code> , it will overwrite an existing <code>CATASTROESP_CACHE_DIR</code> that you already have in local machine.
<code>install</code>	if <code>TRUE</code> , will install the key in your local machine for use in future sessions. Defaults to <code>FALSE</code> . If <code>cache_dir</code> is <code>FALSE</code> this parameter is set to <code>FALSE</code> automatically.
<code>verbose</code>	Logical, displays information. Useful for debugging, default is <code>FALSE</code> .

Value

An (invisible) character with the path to your `cache_dir`.

About caching

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting `update_cache = TRUE`.

If you experience any problem on download, try to download the corresponding file by any other method and save it on your `cache_dir`. Use the option `verbose = TRUE` for debugging the API query.

See Also

`rappdirs::user_config_dir()`

Other cache utilities: `catr_clear_cache()`

Examples

```
# Don't run this! It would modify your current state
## Not run:
catr_set_cache_dir(verbose = TRUE)

## End(Not run)

Sys.getenv("CATASTROESP_CACHE_DIR")
```

catr_srs_values

*Reference SRS codes for **CatastRo** APIs*

Description

A tibble including the valid SRS (also known as CRS) values that may be used on each API service.

Format

A tibble with 16 rows and columns:

- **SRS**: Spatial Reference System (CRS) value, identified by the corresponding **EPSG** code.
- **Description**: Description of the SRS/EPSG code.
- **ovc_service**: Logical. Is this code valid on OVC services?
- **wfs_service**: Logical. Is this code valid on INSPIRE WFS services?

Details

SRS	Description	ovc_service	wfs_service
3785	Web Mercator	FALSE	TRUE
3857	Web Mercator	FALSE	TRUE
4230	Geográficas en ED 50	TRUE	FALSE
4258	Geográficas en ETRS89	TRUE	TRUE
4326	Geográficas en WGS 80	TRUE	TRUE
23029	UTM huso 29N en ED50	TRUE	FALSE
23030	UTM huso 30N en ED50	TRUE	FALSE
23031	UTM huso 31N en ED50	TRUE	FALSE
25829	UTM huso 29N en ETRS89	TRUE	TRUE
25830	UTM huso 30N en ETRS89	TRUE	TRUE
25831	UTM huso 31N en ETRS89	TRUE	TRUE
32627	UTM huso 27N en WGS 84	TRUE	FALSE

32628	UTM huso 28N en WGS 84	TRUE	FALSE
32629	UTM huso 29N en WGS 84	TRUE	FALSE
32630	UTM huso 30N en WGS 84	TRUE	FALSE
32631	UTM huso 31N en WGS 84	TRUE	FALSE

References

- [OVCCoordenadas](#)
- [INSPIRE WFS Service](#)

See Also

Other databases: [catr_atom_get_address_db_all\(\)](#), [catr_atom_get_buildings_db_all\(\)](#), [catr_atom_get_parcelas_db_all\(\)](#), [catr_atom_search_munic\(\)](#)

Other INSPIRE WFS services: [catr_wfs_get_address_bbox\(\)](#), [catr_wfs_get_buildings_bbox\(\)](#), [catr_wfs_get_parcelas_bbox\(\)](#)

OVCCoordenadas API: [catr_ovc_get_cpmrc\(\)](#), [catr_ovc_get_rccoor_distancia\(\)](#), [catr_ovc_get_rccoor\(\)](#)

Examples

```
data(catr_srs_values)

# OVC valid codes
library(dplyr)

catr_srs_values %>% filter(ovc_service == TRUE)

# WFS valid codes

catr_srs_values %>% filter(ovc_service == TRUE)
```

```
catr_wfs_get_address_bbox
```

WFS INSPIRE: Download Addresses

Description

Get the spatial data of addresses The WFS Service allows to perform several types of queries:

- By bounding box: Implemented on [catr_wfs_get_address_bbox\(\)](#). Extract objects included on the bounding box provided. See **Details**.
- By street code: Implemented on [catr_wfs_get_address_codvia\(\)](#). Extract objects of specific addresses.

- By cadastral reference: Implemented on `catr_wfs_get_address_rc()`. Extract objects of specific cadastral references
- By postal codes: Implemented on `catr_wfs_get_address_postalcode()`. Extract objects of specific cadastral references

Check the [API Docs](#).

Usage

```
catr_wfs_get_address_bbox(x, srs, verbose = FALSE)
```

```
catr_wfs_get_address_codvia(codvia, del, mun, srs = NULL, verbose = FALSE)
```

```
catr_wfs_get_address_rc(rc, srs = NULL, verbose = FALSE)
```

```
catr_wfs_get_address_postalcode(postalcode, srs = NULL, verbose = FALSE)
```

Arguments

<code>x</code>	See Details . It could be: <ul style="list-style-type: none"> • A numeric vector of length 4 with the coordinates that defines the bounding box: <code>c(xmin, ymin, xmax, ymax)</code> • A <code>sf/sfc</code> object, as provided by the <code>sf</code> package.
<code>srs</code>	SRS/CRS to use on the query. To check the admitted values check catr_srs_values , specifically the <code>wfs_service</code> column. See Details .
<code>verbose</code>	Logical, displays information. Useful for debugging, default is <code>FALSE</code> .
<code>codvia</code>	Cadastral street code.
<code>del</code>	Cadastral office code.
<code>mun</code>	Cadastral municipality code.
<code>rc</code>	The cadastral reference to be extracted.
<code>postalcode</code>	Postal code.

Details

When `x` is a numeric vector, make sure that the `srs` matches the coordinate values. Additionally, when the `srs` correspond to a geographic reference system (4326, 4258), the function queries the bounding box on [EPSG:3857](#) - Web Mercator, to overcome a potential bug on the API side.

When `x` is a `sf` object, the value `srs` is ignored. In this case, the bounding box of the `sf` object would be used for the query (see `sf::st_bbox()`). The query is performed using [EPSG:3857](#) (Web Mercator). The result is provided always in the SRS of the `sf` object provided as input.

Value

A `sf` object.

API Limits

The API service is limited to a bounding box of 4km² and a maximum of 5.000 elements.

References

[API Documentation](#)

[INSPIRE Services for Cadastral Cartography](#)

See Also

[sf::st_bbox\(\)](#)

INSPIRE API functions: [catr_atom_get_address_db_all\(\)](#), [catr_atom_get_address\(\)](#), [catr_atom_get_buildings_db_all\(\)](#), [catr_atom_get_buildings\(\)](#), [catr_atom_get_parcel_db_all\(\)](#), [catr_atom_get_parcel\(\)](#), [catr_wfs_get_buildings_bbox\(\)](#), [catr_wfs_get_parcel_bbox\(\)](#), [catr_wms_get_layer\(\)](#)

Other INSPIRE WFS services: [catr_srs_values](#), [catr_wfs_get_buildings_bbox\(\)](#), [catr_wfs_get_parcel_bbox\(\)](#)

Other addresses: [catr_atom_get_address_db_all\(\)](#), [catr_atom_get_address\(\)](#)

Other spatial: [catr_atom_get_address\(\)](#), [catr_atom_get_buildings\(\)](#), [catr_atom_get_parcel\(\)](#), [catr_wfs_get_buildings_bbox\(\)](#), [catr_wfs_get_parcel_bbox\(\)](#), [catr_wms_get_layer\(\)](#)

Examples

```
ad <- catr_wfs_get_address_bbox(c(
  233673, 4015968, 233761, 4016008
),
srs = 25830
)
```

```
library(ggplot2)
```

```
ggplot(ad) +
  geom_sf()
```

catr_wfs_get_buildings_bbox

WFS INSPIRE: Download Buildings

Description

Get the spatial data of buildings. The WFS Service allows to perform two types of queries:

- By bounding box: Implemented on [catr_wfs_get_buildings_bbox\(\)](#). Extract objects included on the bounding box provided. See **Details**.

- By cadastral reference: Implemented on `catr_wfs_get_buildings_rc()`. Extract objects of specific cadastral references.

Check the [API Docs](#).

Usage

```
catr_wfs_get_buildings_bbox(x, what = "building", srs, verbose = FALSE)
```

```
catr_wfs_get_buildings_rc(rc, what = "building", srs = NULL, verbose = FALSE)
```

Arguments

<code>x</code>	See Details . It could be: <ul style="list-style-type: none"> • A numeric vector of length 4 with the coordinates that defines the bounding box: <code>c(xmin, ymin, xmax, ymax)</code> • A <code>sf/sfc</code> object, as provided by the <code>sf</code> package.
<code>what</code>	Information to load. It could be "building" for buildings, "buildingpart" for parts of a building or "other" for others (swimming pools, etc.).
<code>srs</code>	SRS/CRS to use on the query. To check the admitted values check catr_srs_values , specifically the <code>wfs_service</code> column. See Details .
<code>verbose</code>	Logical, displays information. Useful for debugging, default is FALSE.
<code>rc</code>	The cadastral reference to be extracted.

Details

When `x` is a numeric vector, make sure that the `srs` matches the coordinate values. Additionally, when the `srs` correspond to a geographic reference system (4326, 4258), the function queries the bounding box on [EPSG:3857](#) - Web Mercator, to overcome a potential bug on the API side. The result is provided always in the SRS provided in `srs`.

When `x` is a `sf` object, the value `srs` is ignored. The query is performed using [EPSG:3857](#) (Web Mercator) and the spatial object is projected back to the SRS of the initial object.

Value

A `sf` object.

API Limits

The API service is limited to a bounding box of 4km² and a maximum of 5.000 elements.

References

[API Documentation](#)

[INSPIRE Services for Cadastral Cartography](#)

See Also

[sf::st_bbox\(\)](#)

INSPIRE API functions: [catr_atom_get_address_db_all\(\)](#), [catr_atom_get_address\(\)](#), [catr_atom_get_buildings_db_all\(\)](#), [catr_atom_get_buildings\(\)](#), [catr_atom_get_parcel_bboxes_db_all\(\)](#), [catr_atom_get_parcel_bboxes\(\)](#), [catr_wfs_get_address_bbox\(\)](#), [catr_wfs_get_parcel_bboxes_bbox\(\)](#), [catr_wms_get_layer\(\)](#)

Other INSPIRE WFS services: [catr_srs_values](#), [catr_wfs_get_address_bbox\(\)](#), [catr_wfs_get_parcel_bboxes_bbox\(\)](#)

Other buildings: [catr_atom_get_buildings_db_all\(\)](#), [catr_atom_get_buildings\(\)](#)

Other spatial: [catr_atom_get_address\(\)](#), [catr_atom_get_buildings\(\)](#), [catr_atom_get_parcel_bboxes\(\)](#), [catr_wfs_get_address_bbox\(\)](#), [catr_wfs_get_parcel_bboxes_bbox\(\)](#), [catr_wms_get_layer\(\)](#)

Examples

```
# Using bbox
building <- catr_wfs_get_buildings_bbox(c(
  376550,
  4545424,
  376600,
  4545474
),
srs = 25830
)
library(ggplot2)
ggplot(building) +
  geom_sf() +
  labs(title = "Search using bbox")

# Using rc
rc <- catr_wfs_get_buildings_rc("6656601UL7465N")
library(ggplot2)
ggplot(rc) +
  geom_sf() +
  labs(title = "Search using rc")
```

catr_wfs_get_parcel_bbox

WFS INSPIRE: Download Cadastral Parcels

Description

Get the spatial data of cadastral parcels and zones. The WFS Service allows to perform several types of queries:

- By bounding box: Implemented on [catr_wfs_get_parcel_bboxes_bbox\(\)](#). Extract objects included on the bounding box provided. See **Details**.

- By zoning: Implemented on `catr_wfs_get_parcel_zoning()`. Extract objects of a specific cadastral zone.
- By cadastral parcel: Implemented on `catr_wfs_get_parcel_parcel()`. Extract cadastral parcels of a specific cadastral reference.
- Neighbor cadastral parcels: Implemented on `catr_wfs_get_parcel_neigh_parcel()`. Extract neighbor cadastral parcels of a specific cadastral reference.
- Cadastral parcels by zoning: Implemented on `catr_wfs_get_parcel_parcel_zoning()`. Extract cadastral parcels of a specific cadastral zone.

Check the [API Docs](#).

Usage

```
catr_wfs_get_parcel_bbox(x, what = "parcel", srs, verbose = FALSE)
```

```
catr_wfs_get_parcel_zoning(cod_zona, srs = NULL, verbose = FALSE)
```

```
catr_wfs_get_parcel_parcel(rc, srs = NULL, verbose = FALSE)
```

```
catr_wfs_get_parcel_neigh_parcel(rc, srs = NULL, verbose = FALSE)
```

```
catr_wfs_get_parcel_parcel_zoning(cod_zona, srs = NULL, verbose = FALSE)
```

Arguments

<code>x</code>	See Details . It could be: <ul style="list-style-type: none"> • A numeric vector of length 4 with the coordinates that defines the bounding box: <code>c(xmin, ymin, xmax, ymax)</code> • A <code>sf/sfc</code> object, as provided by the <code>sf</code> package.
<code>what</code>	Information to load. It could be "parcel" for cadastral parcels or "zoning" for cadastral zoning.
<code>srs</code>	SRS/CRS to use on the query. To check the admitted values check catr_srs_values , specifically the <code>wfs_service</code> column. See Details .
<code>verbose</code>	Logical, displays information. Useful for debugging, default is <code>FALSE</code> .
<code>cod_zona</code>	Cadastral zone code.
<code>rc</code>	The cadastral reference to be extracted.

Details

When `x` is a numeric vector, make sure that the `srs` matches the coordinate values. Additionally, when the `srs` correspond to a geographic reference system (4326, 4258), the function queries the bounding box on [EPSG:3857](#) - Web Mercator, to overcome a potential bug on the API side. The result is provided always in the SRS provided in `srs`.

When `x` is a `sf` object, the value `srs` is ignored. The query is performed using [EPSG:3857](#) (Web Mercator) and the spatial object is projected back to the SRS of the initial object.

Value

A sf object.

API Limits

The API service is limited to the following constraints:

- "parcel": Bounding box of 1km2 and a maximum of 500. elements.
- "zoning": Bounding box of 25km2 and a maximum of 500 elements.

References

[API Documentation](#)

[INSPIRE Services for Cadastral Cartography](#)

See Also

[sf::st_bbox\(\)](#)

INSPIRE API functions: [catr_atom_get_address_db_all\(\)](#), [catr_atom_get_address\(\)](#), [catr_atom_get_buildings_db_all\(\)](#), [catr_atom_get_buildings\(\)](#), [catr_atom_get_parcel_bboxes_db_all\(\)](#), [catr_atom_get_parcel_bboxes\(\)](#), [catr_wfs_get_address_bbox\(\)](#), [catr_wfs_get_buildings_bbox\(\)](#), [catr_wms_get_layer\(\)](#)

Other INSPIRE WFS services: [catr_srs_values](#), [catr_wfs_get_address_bbox\(\)](#), [catr_wfs_get_buildings_bbox\(\)](#)

Other parcels: [catr_atom_get_parcel_bboxes_db_all\(\)](#), [catr_atom_get_parcel_bboxes\(\)](#)

Other spatial: [catr_atom_get_address\(\)](#), [catr_atom_get_buildings\(\)](#), [catr_atom_get_parcel_bboxes\(\)](#), [catr_wfs_get_address_bbox\(\)](#), [catr_wfs_get_buildings_bbox\(\)](#), [catr_wms_get_layer\(\)](#)

Examples

```
cp <- catr_wfs_get_parcel_bbox(c(
  233673, 4015968, 233761, 4016008
),
srs = 25830
)

library(ggplot2)

ggplot(cp) +
  geom_sf()
```

catr_wms_get_layer *WMS INSPIRE: Download map images*

Description

Get geotagged images from the Spanish Cadastre. This function is a wrapper of `mapSpain::esp_getTiles()`.

Usage

```
catr_wms_get_layer(
  x,
  srs,
  what = "building",
  styles = "default",
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE,
  crop = FALSE,
  ...
)
```

Arguments

x	See Details . It could be: <ul style="list-style-type: none"> • A numeric vector of length 4 with the coordinates that defines the bounding box: <code>c(xmin, ymin, xmax, ymax)</code> • A <code>sf/sfc</code> object, as provided by the <code>sf</code> package.
srs	SRS/CRS to use on the query. To check the admitted values check <code>catr_srs_values</code> , specifically the <code>wfs_service</code> column. See Details .
what	Layer to be extracted. Possible values are "building", "parcel", "zoning", "address". See Details .
styles	Style of the WMS layer. See Details .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source file.
cache_dir	A path to a cache directory. On missing value the function would store the cached files on a temporary dir (See <code>base::tempdir()</code>).
verbose	Logical, displays information. Useful for debugging, default is FALSE.
crop	TRUE if results should be cropped to the specified x extent, FALSE otherwise. If x is an <code>sf</code> object with one POINT, crop is set to FALSE.
...	Arguments passed on to <code>mapSpain::esp_getTiles</code>
res	Resolution (in pixels) of the final tile. Only valid for WMS.
bbox_expand	A numeric value that indicates the expansion percentage of the bounding box of x.
transparent	Logical. Provides transparent background, if supported. Depends on the selected provider on type.
mask	TRUE if the result should be masked to x.

Details

When `x` is a numeric vector, make sure that the `srs` matches the coordinate values. When `x` is a `sf` object, the value `srs` is ignored.

The query is performed using [EPSG:3857](#) (Web Mercator) and the spatial object is projected back to the SRS of the initial object. In case that the tile looks deformed, try either providing `bbox` on [EPSG:3857](#) or projecting your `sf` object to `sf::st_crs(3857)`.

Value

A `SpatRaster` is returned, with 3 (RGB) or 4 (RGBA) layers. See [terra::rast\(\)](#).

Layers

The parameter what defines the layer to be extracted. The equivalence with the [API Docs](#) equivalence is:

- "parcel": CP.CadastralParcel
- "zoning": CP.CadastralZoning
- "building": BU.Building
- "buildingpart": BU.BuildingPart
- "address": AD.Address
- "admboundary": AU.AdministrativeBoundary
- "admunit": AU.AdministrativeUnit

Styles

The WMS service provide different styles on each layer (what parameter). Some of the styles available are:

- "parcel": styles : "BoundariesOnly", "ReferencePointOnly", "ELFCadastre".
- "zoning": styles : "BoundariesOnly", "ELFCadastre".
- "building" and "buildingpart": "ELFCadastre"
- "address": "Number.ELFCadastre"
- "admboundary" y "admunit": "ELFCadastre"

Check the [API Docs](#) for more information.

References

[API Documentation](#)

[INSPIRE Services for Cadastral Cartography](#)

See Also

[mapSpain::esp_getTiles\(\)](#), [tidyterra::geom_spatraster_rgb\(\)](#), [terra::plotRGB\(\)](#).

INSPIRE API functions: [catr_atom_get_address_db_all\(\)](#), [catr_atom_get_address\(\)](#), [catr_atom_get_buildings_db_all\(\)](#), [catr_atom_get_buildings\(\)](#), [catr_atom_get_parcel_db_all\(\)](#), [catr_atom_get_parcel\(\)](#), [catr_wfs_get_address_bbox\(\)](#), [catr_wfs_get_buildings_bbox\(\)](#), [catr_wfs_get_parcel_bbox\(\)](#)

Other spatial: [catr_atom_get_address\(\)](#), [catr_atom_get_buildings\(\)](#), [catr_atom_get_parcel\(\)](#), [catr_wfs_get_address_bbox\(\)](#), [catr_wfs_get_buildings_bbox\(\)](#), [catr_wfs_get_parcel_bbox\(\)](#)

Examples

```
# With a bbox

pict <- catr_wms_get_layer(c(222500, 4019500, 223700, 4020700),
  srs = 25830,
  what = "parcel"
)

library(mapSpain)
library(ggplot2)
library(tidyterra)

ggplot() +
  geom_spatraster_rgb(data = pict)

# With a spatial object

parcels <- catr_wfs_get_parcel_neigh_parcel("3662303TF3136B")

# Transform
parcels <- sf::st_transform(parcels, 3857)

# Use styles

parcels_img <- catr_wms_get_layer(parcels,
  what = "buildingpart",
  bbox_expand = 0.3,
  styles = "ELFCadastre"
)

ggplot() +
  geom_sf(data = parcels, fill = "blue", alpha = 0.5) +
  geom_spatraster_rgb(data = parcels_img)
```

Index

* ATOM

catr_atom_get_address, [2](#)
catr_atom_get_address_db_all, [4](#)
catr_atom_get_buildings, [6](#)
catr_atom_get_buildings_db_all, [7](#)
catr_atom_get_parcel, [9](#)
catr_atom_get_parcel_db_all, [11](#)
catr_atom_search_munic, [13](#)

* INSPIRE

catr_atom_get_address, [2](#)
catr_atom_get_address_db_all, [4](#)
catr_atom_get_buildings, [6](#)
catr_atom_get_buildings_db_all, [7](#)
catr_atom_get_parcel, [9](#)
catr_atom_get_parcel_db_all, [11](#)
catr_wfs_get_address_bbox, [25](#)
catr_wfs_get_buildings_bbox, [27](#)
catr_wfs_get_parcel_bbox, [29](#)
catr_wms_get_layer, [32](#)

* OVCCallejero

catr_ovc_get_cod_munic, [16](#)
catr_ovc_get_cod_provinces, [17](#)

* OVCCoordenadas

catr_ovc_get_cpmrc, [18](#)
catr_ovc_get_rccoor, [20](#)
catr_ovc_get_rccoor_distancia, [21](#)
catr_srs_values, [24](#)

* WFS

catr_srs_values, [24](#)
catr_wfs_get_address_bbox, [25](#)
catr_wfs_get_buildings_bbox, [27](#)
catr_wfs_get_parcel_bbox, [29](#)

* WMS

catr_wms_get_layer, [32](#)

* addresses

catr_atom_get_address, [2](#)
catr_atom_get_address_db_all, [4](#)
catr_wfs_get_address_bbox, [25](#)

* buildings

catr_atom_get_buildings, [6](#)
catr_atom_get_buildings_db_all, [7](#)
catr_wfs_get_buildings_bbox, [27](#)

* cache utilities

catr_clear_cache, [14](#)
catr_set_cache_dir, [23](#)

* cadastral references

catr_ovc_get_cpmrc, [18](#)
catr_ovc_get_rccoor, [20](#)
catr_ovc_get_rccoor_distancia, [21](#)

* databases

catr_atom_get_address_db_all, [4](#)
catr_atom_get_buildings_db_all, [7](#)
catr_atom_get_parcel_db_all, [11](#)
catr_atom_search_munic, [13](#)
catr_srs_values, [24](#)

* parcels

catr_atom_get_parcel, [9](#)
catr_atom_get_parcel_db_all, [11](#)
catr_wfs_get_parcel_bbox, [29](#)

* search

catr_atom_search_munic, [13](#)
catr_get_code_from_coords, [15](#)
catr_ovc_get_cod_munic, [16](#)
catr_ovc_get_cod_provinces, [17](#)

* spatial

catr_atom_get_address, [2](#)
catr_atom_get_buildings, [6](#)
catr_atom_get_parcel, [9](#)
catr_wfs_get_address_bbox, [25](#)
catr_wfs_get_buildings_bbox, [27](#)
catr_wfs_get_parcel_bbox, [29](#)
catr_wms_get_layer, [32](#)

base::grep(), [5](#), [8](#), [12](#)

base::tempdir(), [3](#), [5](#), [6](#), [8](#), [10](#), [12](#), [13](#), [15](#),
[23](#), [32](#)

catr_atom_get_address, [2](#), [5](#), [7](#), [9](#), [10](#), [12](#),
[13](#), [27](#), [29](#), [31](#), [34](#)

- catr_atom_get_address_db_all, [3](#), [4](#), [7](#), [9](#), [10](#), [12](#), [13](#), [25](#), [27](#), [29](#), [31](#), [34](#)
- catr_atom_get_address_db_to
(catr_atom_get_address_db_all), [4](#)
- catr_atom_get_address_to
(catr_atom_get_address_db_all), [4](#)
- catr_atom_get_buildings, [3](#), [5](#), [6](#), [9](#), [10](#), [12](#), [13](#), [27](#), [29](#), [31](#), [34](#)
- catr_atom_get_buildings_db_all, [3](#), [5](#), [7](#), [10](#), [12](#), [13](#), [25](#), [27](#), [29](#), [31](#), [34](#)
- catr_atom_get_buildings_db_to
(catr_atom_get_buildings_db_all), [7](#)
- catr_atom_get_buildings_to
(catr_atom_get_buildings_db_all), [7](#)
- catr_atom_get_parcel, [3](#), [5](#), [7](#), [9](#), [9](#), [12](#), [13](#), [27](#), [29](#), [31](#), [34](#)
- catr_atom_get_parcel_db_all, [3](#), [5](#), [7](#), [9](#), [10](#), [11](#), [13](#), [25](#), [27](#), [29](#), [31](#), [34](#)
- catr_atom_get_parcel_db_to
(catr_atom_get_parcel_db_all), [11](#)
- catr_atom_get_parcel_to
(catr_atom_get_parcel_db_all), [11](#)
- catr_atom_search_munic, [3](#), [5](#), [7](#), [9](#), [10](#), [12](#), [13](#), [16–18](#), [25](#)
- catr_atom_search_munic(), [3](#), [6](#), [10](#)
- catr_clear_cache, [14](#), [24](#)
- catr_get_code_from_coords, [13](#), [15](#), [17](#), [18](#)
- catr_ovc_get_cod_munic, [13](#), [16](#), [16](#), [18](#)
- catr_ovc_get_cod_munic(), [15](#)
- catr_ovc_get_cod_provinces, [13](#), [16](#), [17](#), [17](#)
- catr_ovc_get_cod_provinces(), [16](#)
- catr_ovc_get_cpmrc, [18](#), [21](#), [22](#), [25](#)
- catr_ovc_get_rccoor, [19](#), [20](#), [22](#), [25](#)
- catr_ovc_get_rccoor_distancia, [19](#), [21](#), [21](#), [25](#)
- catr_set_cache_dir, [14](#), [23](#)
- catr_set_cache_dir(), [3](#), [4](#), [6](#), [8](#), [10](#), [11](#), [13](#)
- catr_srs_values, [5](#), [9](#), [12](#), [13](#), [15](#), [19–22](#), [24](#), [26–32](#)
- catr_wfs_get_address_bbox, [3](#), [5](#), [7](#), [9](#), [10](#), [12](#), [25](#), [25](#), [29](#), [31](#), [34](#)
- catr_wfs_get_address_codvia
(catr_wfs_get_address_bbox), [25](#)
- catr_wfs_get_address_postalcode
(catr_wfs_get_address_bbox), [25](#)
- catr_wfs_get_address_rc
(catr_wfs_get_address_bbox), [25](#)
- catr_wfs_get_buildings_bbox, [3](#), [5](#), [7](#), [9](#), [10](#), [12](#), [25](#), [27](#), [27](#), [31](#), [34](#)
- catr_wfs_get_buildings_rc
(catr_wfs_get_buildings_bbox), [27](#)
- catr_wfs_get_parcel_bbox, [3](#), [5](#), [7](#), [9](#), [10](#), [12](#), [25](#), [27](#), [29](#), [29](#), [34](#)
- catr_wfs_get_parcel_neigh_parcel
(catr_wfs_get_parcel_bbox), [29](#)
- catr_wfs_get_parcel_parcel
(catr_wfs_get_parcel_bbox), [29](#)
- catr_wfs_get_parcel_parcel_zoning
(catr_wfs_get_parcel_bbox), [29](#)
- catr_wfs_get_parcel_zoning
(catr_wfs_get_parcel_bbox), [29](#)
- catr_wms_get_layer, [3](#), [5](#), [7](#), [9](#), [10](#), [12](#), [27](#), [29](#), [31](#), [32](#)
- mapSpain::esp_get_munic(), [17](#)
- mapSpain::esp_get_munic_siane, [15](#)
- mapSpain::esp_get_munic_siane(), [15](#), [16](#)
- mapSpain::esp_getTiles, [32](#)
- mapSpain::esp_getTiles(), [32](#), [34](#)
- rappdirs::user_config_dir(), [24](#)
- sf::st_bbox(), [26](#), [27](#), [29](#), [31](#)
- sf::st_centroid(), [16](#)
- terra::plotRGB(), [34](#)
- terra::rast(), [33](#)
- tidyterra::geom_spatraster_rgb(), [34](#)