

Package ‘pacviz’

August 16, 2022

Title Pac-Man Visualization Package

Version 1.0.2

Description Provides a broad-view perspective on data via linear mapping of data onto a radial coordinate system. The package contains functions to visualize the residual values of linear regression and Cartesian data in the defined radial scheme. See the ‘pacviz’ documentation page for more information: [<https://pacviz.sriley.dev/>](https://pacviz.sriley.dev/).

License MIT + file LICENSE

Depends R (>= 4.0.0)

Imports circlize, e1071, graphics, plotrix, stats, utils

Suggests knitr, markdown

VignetteBuilder knitr

Encoding UTF-8

RoxygenNote 7.1.1

NeedsCompilation no

Author Spencer Riley [aut, cre]

Maintainer Spencer Riley <academic@sriley.dev>

Repository CRAN

Date/Publication 2022-08-16 07:10:02 UTC

R topics documented:

deg2rad	2
linMap	2
pac.plot	3
pac.resid	3
rad2deg	4
svm.partition	5
unit_format	5

Index	7
--------------	----------

`deg2rad`*Degree angle conversion*

Description

Conversion between degrees and radians

Usage`deg2rad(deg)`**Arguments**

`deg` Angle in degrees

Value

Angle in radians

`linMap`*Linear map*

Description

A function that will map a range of values to a different set of values.

Usage`linMap(x, i, f)`**Arguments**

`x` Range of values to be mapped

`i` Lowest value

`f` Largest value

Value

A set of values spanning from `i` to `f`

pac.plot *Pac-Man plotting function*

Description

A method of plotting traditional Cartesian data, based on a restricted radial coordinate system, while preserving the information.

Usage

```
pac.plot(x, y, title, taxis, raxis, color1 = "gold")
```

Arguments

x, y	Numeric data
title	Figure title
taxis, raxis	Vector with the first entry being the axis label and the second entry being units
color1	Color value as string or rgb

Value

Pac-Man SVM

Examples

```
# Generic Pac-Man plot
data("cars")
pac.plot(cars$dist, cars$speed, 'Example 1', c("Distance", "m"), c("Speed", "m/s"))
```

pac.resid *Pac-Man Residual Function*

Description

A visualization technique in R for regression analysis results, specifically residual values, based on a restricted radial coordinate system. It provides a broad view perspective on the performance of regression models, and supports most model inputs.

Usage

```
pac.resid(
  x,
  y,
  title,
  taxis,
  model = lm(y ~ x, data = data.frame(x, y)),
  color1 = "gold",
  standardize = FALSE
)
```

Arguments

<code>x, y</code>	Numeric data
<code>title</code>	Figure title
<code>taxis</code>	Vector with the first entry being the axis label and the second entry being units
<code>model</code>	An object for which the extraction of model residuals is meaningful.
<code>color1</code>	Color value as string or rgb
<code>standardize</code>	Boolean to standardize the residual value

Value

Pac-Man residual plot

Examples

```
data("cars")
x <- cars$dist
y <- cars$speed
pac.resid(x,y, 'Example 2',
          c("Temperature", 'degC'),
          color1="lightblue",
          standardize=TRUE)
```

rad2deg

Radian angle conversion

Description

Conversion between radians and degrees

Usage

```
rad2deg(rad)
```

Arguments

rad Angle in radians

Value

Angle in degrees

svm.partition	<i>Machine learning data partition</i>
---------------	--

Description

A method of partitioning data between training and testing sets based on the fraction of data used for training

Usage

```
## S3 method for class 'partition'
svm(x, y, l, train_size = 0.7, rand_state = sample(1:2^15, 1))
```

Arguments

x, y Numeric data
 l Numeric labels data
 train_size Fraction of total data that the SVM will train on
 rand_state Value of the random state used to set the seed

Value

Two data frames and a list of indices for the training set

unit_format	<i>Unit formatting</i>
-------------	------------------------

Description

Converts unit inputs into a format that can be displayed. Support is restricted to 'degC', 'degF'.

Usage

```
unit_format(unit)
```

Arguments

unit Unit input

Value

A list of formatted units

Index

- * **conversion**

- deg2rad, 2

- rad2deg, 4

- * **data**

- svm.partition, 5

- * **machine-learning**

- svm.partition, 5

- * **regression**

- pac.resid, 3

- * **visualization**

- pac.plot, 3

- pac.resid, 3

deg2rad, 2

linMap, 2

pac.plot, 3

pac.resid, 3

rad2deg, 4

svm.partition, 5

unit_format, 5