

# Package ‘tipr’

September 5, 2022

**Type** Package

**Title** Tipping Point Analyses

**Version** 1.0.1

**Description** The strength of evidence provided by epidemiological and observational studies is inherently limited by the potential for unmeasured confounding. We focus on three key quantities: the observed bound of the confidence interval closest to the null, the relationship between an unmeasured confounder and the outcome, for example a plausible residual effect size for an unmeasured continuous or binary confounder, and the relationship between an unmeasured confounder and the exposure, for example a realistic mean difference or prevalence difference for this hypothetical confounder between exposure groups. Building on the methods put forth by Cornfield et al. (1959), Bross (1966), Schlesselman (1978), Rosenbaum & Rubin (1983), Lin et al. (1998), Lash et al. (2009), Rosenbaum (1986), Cinelli & Hazlett (2020), VanderWeele & Ding (2017), and Ding & VanderWeele (2016), we can use these quantities to assess how an unmeasured confounder may tip our result to insignificance.

**License** MIT + file LICENSE

**Encoding** UTF-8

**RoxygenNote** 7.1.2

**BugReports** <https://github.com/LucyMcGowan/tipr/issues>

**Suggests** testthat, broom, dplyr, MASS

**Imports** glue, tibble, purrr, sensemakr

**Depends** R (>= 2.10)

**LazyData** true

**NeedsCompilation** no

**Author** Lucy D'Agostino McGowan [aut, cre]  
(<https://orcid.org/0000-0002-6983-2759>)

**Maintainer** Lucy D'Agostino McGowan <lucydagostino@gmail.com>

**Repository** CRAN

**Date/Publication** 2022-09-05 12:50:02 UTC

**R topics documented:**

|                            |           |
|----------------------------|-----------|
| adjust_coef                | 2         |
| adjust_coef_with_binary    | 3         |
| adjust_coef_with_r2        | 4         |
| adjust_hr                  | 6         |
| adjust_hr_with_binary      | 7         |
| adjust_or                  | 8         |
| adjust_or_with_binary      | 9         |
| adjust_rr                  | 10        |
| adjust_rr_with_binary      | 11        |
| exdata_continuous          | 12        |
| exdata_rr                  | 12        |
| e_value                    | 13        |
| observed_bias_order        | 13        |
| observed_bias_tbl          | 14        |
| observed_bias_tip          | 15        |
| observed_covariate_e_value | 16        |
| r_value                    | 16        |
| tip                        | 17        |
| tipr                       | 19        |
| tip_coef                   | 19        |
| tip_coef_with_r2           | 21        |
| tip_hr                     | 22        |
| tip_hr_with_binary         | 23        |
| tip_or                     | 24        |
| tip_or_with_binary         | 26        |
| tip_rr                     | 27        |
| tip_rr_with_binary         | 28        |
| tip_with_binary            | 29        |
| <b>Index</b>               | <b>32</b> |

---

|             |  |
|-------------|--|
| adjust_coef | <i>Adjust an observed regression coefficient for a normally distributed confounder</i> |
|-------------|--|

---

**Description**

Adjust an observed regression coefficient for a normally distributed confounder

**Usage**

```
adjust_coef(
  effect_observed,
  exposure_confounder_effect,
  confounder_outcome_effect,
  verbose = TRUE
```

```

)

adjust_coef_with_continuous(
  effect_observed,
  exposure_confounder_effect,
  confounder_outcome_effect,
  verbose = TRUE
)

```

### Arguments

`effect_observed` Numeric. Observed exposure - outcome effect from a regression model. This can be the beta coefficient, the lower confidence bound of the beta coefficient, or the upper confidence bound of the beta coefficient.

`exposure_confounder_effect` Numeric. Estimated difference in scaled means between the unmeasured confounder in the exposed population and unexposed population

`confounder_outcome_effect` Numeric. Estimated relationship between the unmeasured confounder and the outcome.

`verbose` Logical. Indicates whether to print informative message. Default: TRUE

### Value

Data frame.

### Examples

```

## Update an observed coefficient of 0.5 with an unmeasured confounder
## with a difference in scaled means between exposure groups of 0.2
## and coefficient of 0.3
adjust_coef(0.5, 0.2, 0.3)

```

---

```
adjust_coef_with_binary
```

*Adjust an observed coefficient from a loglinear model with a binary confounder*

---

### Description

Adjust an observed coefficient from a loglinear model with a binary confounder

**Usage**

```
adjust_coef_with_binary(
  effect_observed,
  exposed_confounder_prev,
  unexposed_confounder_prev,
  confounder_outcome_effect,
  verbose = TRUE
)
```

**Arguments**

`effect_observed` Numeric. Observed exposure - outcome effect from a loglinear model. This can be the beta coefficient, the lower confidence bound of the beta coefficient, or the upper confidence bound of the beta coefficient.

`exposed_confounder_prev` Numeric between 0 and 1. Estimated prevalence of the unmeasured confounder in the exposed population

`unexposed_confounder_prev` Numeric between 0 and 1. Estimated prevalence of the unmeasured confounder in the unexposed population

`confounder_outcome_effect` Numeric. Estimated relationship between the unmeasured confounder and the outcome.

`verbose` Logical. Indicates whether to print informative message. Default: TRUE

**Value**

Data frame.

**Examples**

```
adjust_coef_with_binary(1.1, 0.5, 0.3, 1.3)
```

---

`adjust_coef_with_r2` *Adjust a regression coefficient using the partial R2 for an unmeasured confounder-exposure relationship and unmeasured confounder-outcome relationship*

---

**Description**

This function wraps the `sensemkr::adjusted_estimate()` and `sensemkr::adjusted_se()` functions.

**Usage**

```
adjust_coef_with_r2(
  effect_observed,
  se,
  df,
  confounder_exposure_r2,
  confounder_outcome_r2,
  verbose = TRUE,
  alpha = 0.05,
  ...
)
```

**Arguments**

|                        |  |
|------------------------|--|
| effect_observed        | Numeric. Observed exposure - outcome effect from a regression model. This is the point estimate (beta coefficient)   |
| se                     | Numeric. Standard error of the effect_observed in the previous parameter.  |
| df                     | Numeric positive value. Residual degrees of freedom for the model used to estimate the observed exposure - outcome effect. This is the total number of observations minus the number of parameters estimated in your model. Often for models estimated with an intercept this is $N - k - 1$ where $k$ is the number of predictors in the model. |
| confounder_exposure_r2 | Numeric value between 0 and 1. The assumed partial R <sup>2</sup> of the unobserved confounder with the exposure given the measured covariates.  |
| confounder_outcome_r2  | Numeric value between 0 and 1. The assumed partial R <sup>2</sup> of the unobserved confounder with the outcome given the exposure and the measured covariates.  |
| verbose                | Logical. Indicates whether to print informative message. Default: TRUE   |
| alpha                  | Significance level. Default = 0.05.  |
| ...                    | Optional arguments passed to the <a href="#">sensemakr::adjusted_estimate()</a> function.  |

**Value**

A data frame.

**References**

Carlos Cinelli, Jeremy Ferwerda and Chad Hazlett (2021). sensemakr: Sensitivity Analysis Tools for Regression Models. R package version 0.1.4. <https://CRAN.R-project.org/package=sensemakr>

**Examples**

```
adjust_coef_with_r2(0.5, 0.1, 102, 0.05, 0.1)
```

adjust\_hr

*Adjust an observed hazard ratio for a normally distributed confounder***Description**

Adjust an observed hazard ratio for a normally distributed confounder

**Usage**

```
adjust_hr(
  effect_observed,
  exposure_confounder_effect,
  confounder_outcome_effect,
  verbose = TRUE,
  hr_correction = FALSE
)
```

```
adjust_hr_with_continuous(
  effect_observed,
  exposure_confounder_effect,
  confounder_outcome_effect,
  verbose = TRUE,
  hr_correction = FALSE
)
```

**Arguments**

|                            |   |
|----------------------------|---|
| effect_observed            | Numeric positive value. Observed exposure - outcome hazard ratio. This can be the point estimate, lower confidence bound, or upper confidence bound.  |
| exposure_confounder_effect | Numeric. Estimated difference in scaled means between the unmeasured confounder in the exposed population and unexposed population  |
| confounder_outcome_effect  | Numeric. Estimated relationship between the unmeasured confounder and the outcome.  |
| verbose                    | Logical. Indicates whether to print informative message. Default: TRUE  |
| hr_correction              | Logical. Indicates whether to use a correction factor. The methods used for this function are based on risk ratios. For rare outcomes, a hazard ratio approximates a risk ratio. For common outcomes, a correction factor is needed. If you have a common outcome (>15%), set this to TRUE. Default: FALSE. |

**Value**

Data frame.

**Examples**

```
adjust_hr(0.9, -0.9, 1.3)
```

---

```
adjust_hr_with_binary Adjust an observed hazard ratio with a binary confounder
```

---

**Description**

Adjust an observed hazard ratio with a binary confounder

**Usage**

```
adjust_hr_with_binary(  
  effect_observed,  
  exposed_confounder_prev,  
  unexposed_confounder_prev,  
  confounder_outcome_effect,  
  verbose = TRUE,  
  hr_correction = FALSE  
)
```

**Arguments**

|                           |   |
|---------------------------|---|
| effect_observed           | Numeric positive value. Observed exposure - outcome hazard ratio. This can be the point estimate, lower confidence bound, or upper confidence bound.  |
| exposed_confounder_prev   | Numeric between 0 and 1. Estimated prevalence of the unmeasured confounder in the exposed population  |
| unexposed_confounder_prev | Numeric between 0 and 1. Estimated prevalence of the unmeasured confounder in the unexposed population  |
| confounder_outcome_effect | Numeric positive value. Estimated relationship between the unmeasured confounder and the outcome  |
| verbose                   | Logical. Indicates whether to print informative message. Default: TRUE  |
| hr_correction             | Logical. Indicates whether to use a correction factor. The methods used for this function are based on risk ratios. For rare outcomes, a hazard ratio approximates a risk ratio. For common outcomes, a correction factor is needed. If you have a common outcome (>15%), set this to TRUE. Default: FALSE. |

**Value**

Data frame.

**Examples**

```
adjust_hr_with_binary(0.8, 0.1, 0.5, 1.8)
```

---

`adjust_or`*Adjust an observed odds ratio for a normally distributed confounder*

---

**Description**

Adjust an observed odds ratio for a normally distributed confounder

**Usage**

```
adjust_or(  
  effect_observed,  
  exposure_confounder_effect,  
  confounder_outcome_effect,  
  verbose = TRUE,  
  or_correction = FALSE  
)
```

```
adjust_or_with_continuous(  
  effect_observed,  
  exposure_confounder_effect,  
  confounder_outcome_effect,  
  verbose = TRUE,  
  or_correction = FALSE  
)
```

**Arguments**

|   |  |
|---|--|
| <code>effect_observed</code>            | Numeric positive value. Observed exposure - outcome odds ratio. This can be the point estimate, lower confidence bound, or upper confidence bound.   |
| <code>exposure_confounder_effect</code> | Numeric. Estimated difference in scaled means between the unmeasured confounder in the exposed population and unexposed population   |
| <code>confounder_outcome_effect</code>  | Numeric. Estimated relationship between the unmeasured confounder and the outcome.   |
| <code>verbose</code>                    | Logical. Indicates whether to print informative message. Default: TRUE   |
| <code>or_correction</code>              | Logical. Indicates whether to use a correction factor. The methods used for this function are based on risk ratios. For rare outcomes, an odds ratio approximates a risk ratio. For common outcomes, a correction factor is needed. If you have a common outcome (>15%), set this to TRUE. Default: FALSE. |

**Value**

Data frame.

**Examples**

```
adjust_or(1.2, 0.9, 1.3)
```

---

adjust\_or\_with\_binary *Adjust an observed odds ratio with a binary confounder*

---

**Description**

Adjust an observed odds ratio with a binary confounder

**Usage**

```
adjust_or_with_binary(
  effect_observed,
  exposed_confounder_prev,
  unexposed_confounder_prev,
  confounder_outcome_effect,
  verbose = TRUE,
  or_correction = FALSE
)
```

**Arguments**

|                           |  |
|---------------------------|--|
| effect_observed           | Numeric positive value. Observed exposure - outcome odds ratio. This can be the point estimate, lower confidence bound, or upper confidence bound.   |
| exposed_confounder_prev   | Numeric between 0 and 1. Estimated prevalence of the unmeasured confounder in the exposed population   |
| unexposed_confounder_prev | Numeric between 0 and 1. Estimated prevalence of the unmeasured confounder in the unexposed population   |
| confounder_outcome_effect | Numeric positive value. Estimated relationship between the unmeasured confounder and the outcome   |
| verbose                   | Logical. Indicates whether to print informative message. Default: TRUE   |
| or_correction             | Logical. Indicates whether to use a correction factor. The methods used for this function are based on risk ratios. For rare outcomes, an odds ratio approximates a risk ratio. For common outcomes, a correction factor is needed. If you have a common outcome (>15%), set this to TRUE. Default: FALSE. |

**Value**

Data frame.

**Examples**

```
adjust_or_with_binary(3, 1, 0, 3)
adjust_or_with_binary(3, 1, 0, 3, or_correction = TRUE)
```

---

|           |  |
|-----------|--|
| adjust_rr | <i>Adjust an observed risk ratio for a normally distributed confounder</i> |
|-----------|--|

---

**Description**

Adjust an observed risk ratio for a normally distributed confounder

**Usage**

```
adjust_rr(
  effect_observed,
  exposure_confounder_effect,
  confounder_outcome_effect,
  verbose = TRUE
)

adjust_rr_with_continuous(
  effect_observed,
  exposure_confounder_effect,
  confounder_outcome_effect,
  verbose = TRUE
)
```

**Arguments**

|                            |  |
|----------------------------|--|
| effect_observed            | Numeric positive value. Observed exposure - outcome risk ratio. This can be the point estimate, lower confidence bound, or upper confidence bound. |
| exposure_confounder_effect | Numeric. Estimated difference in scaled means between the unmeasured confounder in the exposed population and unexposed population                 |
| confounder_outcome_effect  | Numeric. Estimated relationship between the unmeasured confounder and the outcome.   |
| verbose                    | Logical. Indicates whether to print informative message. Default: TRUE   |

**Value**

Data frame.

**Examples**

```
adjust_rr(1.2, 0.5, 1.1)
```

---

adjust\_rr\_with\_binary *Adjust an observed risk ratio with a binary confounder*

---

## Description

Adjust an observed risk ratio with a binary confounder

## Usage

```
adjust_rr_with_binary(  
  effect_observed,  
  exposed_confounder_prev,  
  unexposed_confounder_prev,  
  confounder_outcome_effect,  
  verbose = TRUE  
)
```

## Arguments

|                           |  |
|---------------------------|--|
| effect_observed           | Numeric positive value. Observed exposure - outcome risk ratio. This can be the point estimate, lower confidence bound, or upper confidence bound. |
| exposed_confounder_prev   | Numeric between 0 and 1. Estimated prevalence of the unmeasured confounder in the exposed population   |
| unexposed_confounder_prev | Numeric between 0 and 1. Estimated prevalence of the unmeasured confounder in the unexposed population   |
| confounder_outcome_effect | Numeric positive value. Estimated relationship between the unmeasured confounder and the outcome   |
| verbose                   | Logical. Indicates whether to print informative message. Default: TRUE   |

## Value

Data frame.

## Examples

```
adjust_rr_with_binary(1.1, 0.5, 0.3, 1.3)
```

---

|                   |  |
|-------------------|--|
| exdata_continuous | <i>Example Data (Continuous Outcome)</i> |
|-------------------|--|

---

**Description**

A data set simulated with two Normally distributed confounders, one "measured" and one "unmeasured", an exposure, and outcome. The "true" causal effect of the exposure on the outcome, accounting for both the measured and unmeasured confounders, should be 0.

**Usage**

```
exdata_continuous
```

**Format**

A data frame with 2,000 rows and 4 columns:

- .unmeasured\_confounder: A simulated unmeasured confounder
- measured\_confounder: A simulated measured confounder
- exposure
- outcome

---

|           |                                  |
|-----------|----------------------------------|
| exdata_rr | <i>Example Data (Risk Ratio)</i> |
|-----------|----------------------------------|

---

**Description**

A data set simulated with two Normally distributed confounders, one "measured" and one "unmeasured", an exposure, and outcome. The "true" causal effect of the exposure on the outcome, accounting for both the measured and unmeasured confounders, should be 0.

**Usage**

```
exdata_rr
```

**Format**

A data frame with 2,000 rows and 4 columns:

- .unmeasured\_confounder: A simulated unmeasured confounder
- measured\_confounder: A simulated measured confounder
- exposure
- outcome

---

|         |                             |
|---------|-----------------------------|
| e_value | <i>Calculate an E-value</i> |
|---------|-----------------------------|

---

**Description**

Calculate an E-value

**Usage**

```
e_value(effect_observed)
```

**Arguments**

effect\_observed

Numeric positive value. Observed exposure - outcome effect (assumed to be the exponentiated coefficient, so a risk ratio, odds ratio, or hazard ratio). This can be the point estimate, lower confidence bound, or upper confidence bound.

**Value**

Numeric value

**Examples**

```
e_value(0.9)
e_value(1.3)
```

---

|                     |  |
|---------------------|--|
| observed_bias_order | <i>Order observed bias data frame for plotting</i> |
|---------------------|--|

---

**Description**

Order observed bias data frame for plotting

**Usage**

```
observed_bias_order(d, by)
```

**Arguments**

d Observed bias data frame. Must have columns dropped and type  
by Character. Variable in d to order by.

**Value**

Data frame in the correct order

---

observed\_bias\_tbl      *Create a data frame to assist with creating an observed bias plot*

---

### Description

Create a data frame to assist with creating an observed bias plot

### Usage

```
observed_bias_tbl(ps_mod, outcome_mod, drop_list = NULL)
```

### Arguments

|             |  |
|-------------|--|
| ps_mod      | Model object for the propensity score model  |
| outcome_mod | Model object for the outcome model   |
| drop_list   | Named list of covariates or groups of covariates to drop if NULL, will default to dropping each covariate one at a time. |

### Value

Data frame with the following columns:

- dropped: The covariate or group of covariates that were dropped
- type: Explanation of dropped, whether it refers to a single covariate (covariate) or a group of covariates (group)
- ps\_formula: The new formula for the updated propensity score model
- outcome\_formula: The new formula for the updated outcome model
- ps\_model: The new model object for the updated propensity score model
- p: The updated propensity score

### Examples

```
ps_mod <- glm(am ~ mpg + cyl + I(hp^2), data = mtcars)
outcome_mod <- lm(qsec ~ am + hp + disp + wt, data = mtcars)
observed_bias_tbl(
  ps_mod,
  outcome_mod,
  drop_list = list(
    group_one = c("mpg", "hp"),
    group_two = c("cyl", "wt")
  )
)
```

---

|                   |   |
|-------------------|---|
| observed_bias_tip | <i>Create a data frame to combine with an observed bias data frame demonstrating a hypothetical unmeasured confounder</i> |
|-------------------|---|

---

### Description

Create a data frame to combine with an observed bias data frame demonstrating a hypothetical unmeasured confounder

### Usage

```
observed_bias_tip(  
  tip,  
  point_estimate,  
  lb,  
  ub,  
  tip_desc = "Hypothetical unmeasured confounder"  
)
```

### Arguments

|                |  |
|----------------|--|
| tip            | Numeric. Value you would like to tip to.         |
| point_estimate | Numeric. Result estimate from the full model.    |
| lb             | Numeric. Result lower bound from the full model. |
| ub             | Numeric. Result upper bound from the full model. |
| tip_desc       | Character. A description of the tipping point.   |

### Value

A data frame with five columns:

- `dropped`: the input from `tip_desc`
- `type`: Explanation of `dropped`, here `tip` to clarify that this was calculated as a tipping point.
- `point_estimate`: the shifted point estimate
- `lb`: the shifted lower bound
- `ub`: the shifted upper bound

---

observed\_covariate\_e\_value

*Calculate the Observed Covariate E-value*

---

### Description

Calculate the Observed Covariate E-value

### Usage

```
observed_covariate_e_value(lb, ub, lb_adj, ub_adj, transform = NULL)
```

### Arguments

|           |  |
|-----------|--|
| lb        | Numeric. The lower bound of the full model   |
| ub        | Numeric. The upper bound of the full model   |
| lb_adj    | Numeric. The lower bound of the adjusted model   |
| ub_adj    | Numeric. The upper bound of the adjusted model   |
| transform | Character. If your effect is an odds ratio or hazard ratio, this will perform the transformation suggested by VanderWeele and Ding. Allowed values are: <ul style="list-style-type: none"> <li>• "OR"</li> <li>• "HR"</li> </ul> |

### Value

The Observed Covariate E-value

---

r\_value

*Robustness value*

---

### Description

This function wraps the `sensemkr::robustness_value()` function

### Usage

```
r_value(effect_observed, se, df, ...)
```

**Arguments**

|                 |  |
|-----------------|--|
| effect_observed | Numeric. Observed exposure - outcome effect from a regression model. This is the point estimate (beta coefficient)   |
| se              | Numeric. Standard error of the effect_observed in the previous parameter.  |
| df              | Numeric positive value. Residual degrees of freedom for the model used to estimate the observed exposure - outcome effect. This is the total number of observations minus the number of parameters estimated in your model. Often for models estimated with an intercept this is $N - k - 1$ where $k$ is the number of predictors in the model. |
| ...             | Optional arguments passed to the <code>sensemkr::robustness_value()</code> function.   |

**Value**

Numeric. Robustness value

**References**

Carlos Cinelli, Jeremy Ferwerda and Chad Hazlett (2021). `sensemkr`: Sensitivity Analysis Tools for Regression Models. R package version 0.1.4. <https://CRAN.R-project.org/package=sensemkr>

**Examples**

```
r_value(0.5, 0.1, 102)
```

---

tip

*Tip a result with a normally distributed confounder.*

---

**Description**

choose one of the following, and the other will be estimated:

- exposure\_confounder\_effect
- confounder\_outcome\_effect

**Usage**

```
tip(
  effect_observed,
  exposure_confounder_effect = NULL,
  confounder_outcome_effect = NULL,
  verbose = TRUE,
  correction_factor = "none"
)

tip_with_continuous(
```

```

    effect_observed,
    exposure_confounder_effect = NULL,
    confounder_outcome_effect = NULL,
    verbose = TRUE,
    correction_factor = "none"
  )

tip_c(
  effect_observed,
  exposure_confounder_effect = NULL,
  confounder_outcome_effect = NULL,
  verbose = TRUE,
  correction_factor = "none"
)

```

### Arguments

**effect\_observed** Numeric positive value. Observed exposure - outcome effect (assumed to be the exponentiated coefficient, so a risk ratio, odds ratio, or hazard ratio). This can be the point estimate, lower confidence bound, or upper confidence bound.

**exposure\_confounder\_effect** Numeric. Estimated difference in scaled means between the unmeasured confounder in the exposed population and unexposed population

**confounder\_outcome\_effect** Numeric positive value. Estimated relationship between the unmeasured confounder and the outcome

**verbose** Logical. Indicates whether to print informative message. Default: TRUE

**correction\_factor** Character string. Options are "none", "hr", "or". For common outcomes (>15%), the odds ratio or hazard ratio is not a good estimate for the risk ratio. In these cases, we can apply a correction factor. If you are supplying a hazard ratio for a common outcome, set this to "hr"; if you are supplying an odds ratio for a common outcome, set this to "or"; if you are supplying a risk ratio or your outcome is rare, set this to "none" (default).

### Value

Data frame.

### Examples

```

## to estimate the relationship between an unmeasured confounder and outcome
## needed to tip analysis
tip(1.2, exposure_confounder_effect = -2)

## to estimate the number of unmeasured confounders specified needed to tip
## the analysis
tip(1.2, exposure_confounder_effect = -2, confounder_outcome_effect = .99)

```

```
## Example with broom
if (requireNamespace("broom", quietly = TRUE) &&
    requireNamespace("dplyr", quietly = TRUE)) {
  glm(am ~ mpg, data = mtcars, family = "binomial") %>%
  broom::tidy(conf.int = TRUE, exponentiate = TRUE) %>%
  dplyr::filter(term == "mpg") %>%
  dplyr::pull(conf.low) %>%
  tip(confounder_outcome_effect = 2.5)
}
```

---

 tipr

*tipr*


---

## Description

The tipr package.

## References

D'Agostino McGowan, L. (2018). Improving Modern Techniques of Causal Inference: Finite Sample Performance of ATM and ATO Doubly Robust Estimators, Variance Estimation for ATO Estimators, and Contextualized Tipping Point Sensitivity Analyses for Unmeasured Confounding. PhD thesis, Vanderbilt University.

VanderWeele, TJ, and Peng D (2017). Sensitivity Analysis in Observational Research: Introducing the E-Value. *Ann Intern Med*, 167(4), 268–74.

Lin, DY, Psaty, BM, & Kronmal, RA. (1998). Assessing the sensitivity of regression results to unmeasured confounders in observational studies. *Biometrics*, 54(3), 948–963.

---

 tipr\_coef

*Tip a linear model coefficient with a continuous confounder.*


---

## Description

choose one of the following, and the other will be estimated:

- exposure\_confounder\_effect
- confounder\_outcome\_effect

**Usage**

```
tip_coef(
  effect_observed,
  exposure_confounder_effect = NULL,
  confounder_outcome_effect = NULL,
  verbose = TRUE
)

tip_coef_with_continuous(
  effect_observed,
  exposure_confounder_effect = NULL,
  confounder_outcome_effect = NULL,
  verbose = TRUE
)
```

**Arguments**

`effect_observed` Numeric. Observed exposure - outcome effect from a regression model. This can be the beta coefficient, the lower confidence bound of the beta coefficient, or the upper confidence bound of the beta coefficient.

`exposure_confounder_effect` Numeric. Estimated scaled mean difference between the unmeasured confounder in the exposed population and unexposed population

`confounder_outcome_effect` Numeric positive value. Estimated relationship between the unmeasured confounder and the outcome

`verbose` Logical. Indicates whether to print informative message. Default: TRUE

**Value**

Data frame.

**Examples**

```
## to estimate the relationship between an unmeasured confounder and outcome
## needed to tip analysis
tip_coef(1.2, exposure_confounder_effect = -2)

## to estimate the number of unmeasured confounders specified needed to tip
## the analysis
tip_coef(1.2, exposure_confounder_effect = -2, confounder_outcome_effect = -0.05)

## Example with broom
if (requireNamespace("broom", quietly = TRUE) &&
    requireNamespace("dplyr", quietly = TRUE)) {
  lm(wt ~ mpg, data = mtcars) %>%
    broom::tidy(conf.int = TRUE) %>%
    dplyr::filter(term == "mpg") %>%
```

```

dplyr::pull(conf.low) %>%
  tip_coef(confounder_outcome_effect = 2.5)
}

```

---

|                  |  |
|------------------|--|
| tip_coef_with_r2 | <i>Tip a regression coefficient using the partial R2 for an unmeasured confounder-exposure relationship and unmeasured confounder-outcome relationship</i> |
|------------------|--|

---

### Description

Choose one of the following, and the other will be estimated:

- confounder\_exposure\_r2
- confounder\_outcome\_r2

### Usage

```

tip_coef_with_r2(
  effect_observed,
  se,
  df,
  confounder_exposure_r2 = NULL,
  confounder_outcome_r2 = NULL,
  verbose = TRUE,
  alpha = 0.05,
  tip_bound = FALSE,
  ...
)

```

### Arguments

|                        |  |
|------------------------|--|
| effect_observed        | Numeric. Observed exposure - outcome effect from a regression model. This is the point estimate (beta coefficient)   |
| se                     | Numeric. Standard error of the effect_observed in the previous parameter.  |
| df                     | Numeric positive value. Residual degrees of freedom for the model used to estimate the observed exposure - outcome effect. This is the total number of observations minus the number of parameters estimated in your model. Often for models estimated with an intercept this is $N - k - 1$ where $k$ is the number of predictors in the model. |
| confounder_exposure_r2 | Numeric value between 0 and 1. The assumed partial R2 of the unobserved confounder with the exposure given the measured covariates.  |
| confounder_outcome_r2  | Numeric value between 0 and 1. The assumed partial R2 of the unobserved confounder with the outcome given the exposure and the measured covariates.  |

|           |   |
|-----------|---|
| verbose   | Logical. Indicates whether to print informative message. Default: TRUE                |
| alpha     | Significance level. Default = 0.05.   |
| tip_bound | Do you want to tip at the bound? Default = FALSE, will tip at the point estimate      |
| ...       | Optional arguments passed to the <code>sensemkr::adjusted_estimate()</code> function. |

### Value

A data frame.

### Examples

```
tip_coef_with_r2(0.5, 0.1, 102, 0.5)
```

---

|        |   |
|--------|---|
| tip_hr | <i>Tip an observed hazard ratio with a normally distributed confounder.</i> |
|--------|---|

---

### Description

choose one of the following, and the other will be estimated:

- exposure\_confounder\_effect
- confounder\_outcome\_effect

### Usage

```
tip_hr(
  effect_observed,
  exposure_confounder_effect = NULL,
  confounder_outcome_effect = NULL,
  verbose = TRUE,
  hr_correction = FALSE
)

tip_hr_with_continuous(
  effect_observed,
  exposure_confounder_effect = NULL,
  confounder_outcome_effect = NULL,
  verbose = TRUE,
  hr_correction = FALSE
)
```

**Arguments**

|                            |   |
|----------------------------|---|
| effect_observed            | Numeric positive value. Observed exposure - outcome hazard ratio. This can be the point estimate, lower confidence bound, or upper confidence bound.  |
| exposure_confounder_effect | Numeric. Estimated difference in scaled means between the unmeasured confounder in the exposed population and unexposed population  |
| confounder_outcome_effect  | Numeric positive value. Estimated relationship between the unmeasured confounder and the outcome  |
| verbose                    | Logical. Indicates whether to print informative message. Default: TRUE  |
| hr_correction              | Logical. Indicates whether to use a correction factor. The methods used for this function are based on risk ratios. For rare outcomes, a hazard ratio approximates a risk ratio. For common outcomes, a correction factor is needed. If you have a common outcome (>15%), set this to TRUE. Default: FALSE. |

**Value**

Data frame.

**Examples**

```
## to estimate the relationship between an unmeasured confounder and outcome
## needed to tip analysis
tip_hr(1.2, exposure_confounder_effect = -2)

## to estimate the number of unmeasured confounders specified needed to tip
## the analysis
tip_hr(1.2, exposure_confounder_effect = -2, confounder_outcome_effect = .99)
```

---

tip\_hr\_with\_binary      *Tip an observed hazard ratio with a binary confounder.*

---

**Description**

Choose two of the following three to specify, and the third will be estimated:

- exposed\_confounder\_prev
- unexposed\_confounder\_prev
- confounder\_outcome\_effect

Alternatively, specify all three and the function will return the number of unmeasured confounders specified needed to tip the analysis.

**Usage**

```
tip_hr_with_binary(
  effect_observed,
  exposed_confounder_prev = NULL,
  unexposed_confounder_prev = NULL,
  confounder_outcome_effect = NULL,
  verbose = TRUE,
  hr_correction = FALSE
)
```

**Arguments**

|                           |   |
|---------------------------|---|
| effect_observed           | Numeric positive value. Observed exposure - outcome hazard ratio. This can be the point estimate, lower confidence bound, or upper confidence bound.  |
| exposed_confounder_prev   | Numeric between 0 and 1. Estimated prevalence of the unmeasured confounder in the exposed population  |
| unexposed_confounder_prev | Numeric between 0 and 1. Estimated prevalence of the unmeasured confounder in the unexposed population  |
| confounder_outcome_effect | Numeric positive value. Estimated relationship between the unmeasured confounder and the outcome  |
| verbose                   | Logical. Indicates whether to print informative message. Default: TRUE  |
| hr_correction             | Logical. Indicates whether to use a correction factor. The methods used for this function are based on risk ratios. For rare outcomes, a hazard ratio approximates a risk ratio. For common outcomes, a correction factor is needed. If you have a common outcome (>15%), set this to TRUE. Default: FALSE. |

**Value**

Data frame.

**Examples**

```
tip_hr_with_binary(0.9, 0.9, 0.1)
```

---

tip\_or

*Tip an observed odds ratio with a normally distributed confounder.*

---

**Description**

choose one of the following, and the other will be estimated:

- exposure\_confounder\_effect
- confounder\_outcome\_effect

**Usage**

```
tip_or(
  effect_observed,
  exposure_confounder_effect = NULL,
  confounder_outcome_effect = NULL,
  verbose = TRUE,
  or_correction = FALSE
)

tip_or_with_continuous(
  effect_observed,
  exposure_confounder_effect = NULL,
  confounder_outcome_effect = NULL,
  verbose = TRUE,
  or_correction = FALSE
)
```

**Arguments**

**effect\_observed** Numeric positive value. Observed exposure - outcome odds ratio. This can be the point estimate, lower confidence bound, or upper confidence bound.

**exposure\_confounder\_effect** Numeric. Estimated difference in scaled means between the unmeasured confounder in the exposed population and unexposed population

**confounder\_outcome\_effect** Numeric positive value. Estimated relationship between the unmeasured confounder and the outcome

**verbose** Logical. Indicates whether to print informative message. Default: TRUE

**or\_correction** Logical. Indicates whether to use a correction factor. The methods used for this function are based on risk ratios. For rare outcomes, an odds ratio approximates a risk ratio. For common outcomes, a correction factor is needed. If you have a common outcome (>15%), set this to TRUE. Default: FALSE.

**Value**

Data frame.

**Examples**

```
## to estimate the relationship between an unmeasured confounder and outcome
## needed to tip analysis
tip_or(1.2, exposure_confounder_effect = -2)

## to estimate the number of unmeasured confounders specified needed to tip
## the analysis
tip_or(1.2, exposure_confounder_effect = -2, confounder_outcome_effect = .99)
```

```
## Example with broom
if (requireNamespace("broom", quietly = TRUE) &&
    requireNamespace("dplyr", quietly = TRUE)) {
  glm(am ~ mpg, data = mtcars, family = "binomial") %>%
  broom::tidy(conf.int = TRUE, exponentiate = TRUE) %>%
  dplyr::filter(term == "mpg") %>%
  dplyr::pull(conf.low) %>%
  tip_or(confounder_outcome_effect = 2.5, or_correction = TRUE)
}
```

---

tip\_or\_with\_binary      *Tip an observed odds ratio with a binary confounder.*

---

### Description

Choose two of the following three to specify, and the third will be estimated:

- exposed\_confounder\_prev
- unexposed\_confounder\_prev
- confounder\_outcome\_effect

Alternatively, specify all three and the function will return the number of unmeasured confounders specified needed to tip the analysis.

### Usage

```
tip_or_with_binary(
  effect_observed,
  exposed_confounder_prev = NULL,
  unexposed_confounder_prev = NULL,
  confounder_outcome_effect = NULL,
  verbose = TRUE,
  or_correction = FALSE
)
```

### Arguments

- effect\_observed  
Numeric positive value. Observed exposure - outcome odds ratio. This can be the point estimate, lower confidence bound, or upper confidence bound.
- exposed\_confounder\_prev  
Numeric between 0 and 1. Estimated prevalence of the unmeasured confounder in the exposed population
- unexposed\_confounder\_prev  
Numeric between 0 and 1. Estimated prevalence of the unmeasured confounder in the unexposed population

|                           |  |
|---------------------------|--|
| confounder_outcome_effect | Numeric positive value. Estimated relationship between the unmeasured confounder and the outcome   |
| verbose                   | Logical. Indicates whether to print informative message. Default: TRUE   |
| or_correction             | Logical. Indicates whether to use a correction factor. The methods used for this function are based on risk ratios. For rare outcomes, an odds ratio approximates a risk ratio. For common outcomes, a correction factor is needed. If you have a common outcome (>15%), set this to TRUE. Default: FALSE. |

**Value**

Data frame.

**Examples**

```
tip_or_with_binary(0.9, 0.9, 0.1)
```

---

|        |   |
|--------|---|
| tip_rr | <i>Tip an observed risk ratio with a normally distributed confounder.</i> |
|--------|---|

---

**Description**

choose one of the following, and the other will be estimated:

- exposure\_confounder\_effect
- confounder\_outcome\_effect

**Usage**

```
tip_rr(
  effect_observed,
  exposure_confounder_effect = NULL,
  confounder_outcome_effect = NULL,
  verbose = TRUE
)

tip_rr_with_continuous(
  effect_observed,
  exposure_confounder_effect = NULL,
  confounder_outcome_effect = NULL,
  verbose = TRUE
)
```

**Arguments**

|                            |  |
|----------------------------|--|
| effect_observed            | Numeric positive value. Observed exposure - outcome risk ratio. This can be the point estimate, lower confidence bound, or upper confidence bound. |
| exposure_confounder_effect | Numeric. Estimated difference in scaled means between the unmeasured confounder in the exposed population and unexposed population                 |
| confounder_outcome_effect  | Numeric positive value. Estimated relationship between the unmeasured confounder and the outcome   |
| verbose                    | Logical. Indicates whether to print informative message. Default: TRUE   |

**Value**

Data frame.

**Examples**

```
## to estimate the relationship between an unmeasured confounder and outcome
## needed to tip analysis
tip_rr(1.2, exposure_confounder_effect = -2)

## to estimate the number of unmeasured confounders specified needed to tip
## the analysis
tip_rr(1.2, exposure_confounder_effect = -2, confounder_outcome_effect = .99)
```

---

tip\_rr\_with\_binary      *Tip an observed risk ratio with a binary confounder.*

---

**Description**

Choose two of the following three to specify, and the third will be estimated:

- exposed\_confounder\_prev
- unexposed\_confounder\_prev
- confounder\_outcome\_effect

Alternatively, specify all three and the function will return the number of unmeasured confounders specified needed to tip the analysis.

**Usage**

```
tip_rr_with_binary(
  effect_observed,
  exposed_confounder_prev = NULL,
  unexposed_confounder_prev = NULL,
  confounder_outcome_effect = NULL,
  verbose = TRUE
)
```

**Arguments**

|                           |  |
|---------------------------|--|
| effect_observed           | Numeric positive value. Observed exposure - outcome risk ratio. This can be the point estimate, lower confidence bound, or upper confidence bound. |
| exposed_confounder_prev   | Numeric between 0 and 1. Estimated prevalence of the unmeasured confounder in the exposed population   |
| unexposed_confounder_prev | Numeric between 0 and 1. Estimated prevalence of the unmeasured confounder in the unexposed population   |
| confounder_outcome_effect | Numeric positive value. Estimated relationship between the unmeasured confounder and the outcome   |
| verbose                   | Logical. Indicates whether to print informative message. Default: TRUE   |

---

|                 |   |
|-----------------|---|
| tip_with_binary | <i>Tip a result with a binary confounder.</i> |
|-----------------|---|

---

**Description**

Choose two of the following three to specify, and the third will be estimated:

- exposed\_confounder\_prev
- unexposed\_confounder\_prev
- confounder\_outcome\_effect

Alternatively, specify all three and the function will return the number of unmeasured confounders specified needed to tip the analysis.

**Usage**

```
tip_with_binary(
  effect_observed,
  exposed_confounder_prev = NULL,
  unexposed_confounder_prev = NULL,
  confounder_outcome_effect = NULL,
```

```

    verbose = TRUE,
    correction_factor = "none"
  )

  tip_b(
    effect_observed,
    exposed_confounder_prev = NULL,
    unexposed_confounder_prev = NULL,
    confounder_outcome_effect = NULL,
    verbose = TRUE,
    correction_factor = "none"
  )

```

### Arguments

**effect\_observed** Numeric positive value. Observed exposure - outcome effect (assumed to be the exponentiated coefficient, so a risk ratio, odds ratio, or hazard ratio). This can be the point estimate, lower confidence bound, or upper confidence bound.

**exposed\_confounder\_prev** Numeric between 0 and 1. Estimated prevalence of the unmeasured confounder in the exposed population

**unexposed\_confounder\_prev** Numeric between 0 and 1. Estimated prevalence of the unmeasured confounder in the unexposed population

**confounder\_outcome\_effect** Numeric positive value. Estimated relationship between the unmeasured confounder and the outcome

**verbose** Logical. Indicates whether to print informative message. Default: TRUE

**correction\_factor** Character string. Options are "none", "hr", "or". For common outcomes (>15%), the odds ratio or hazard ratio is not a good estimate for the risk ratio. In these cases, we can apply a correction factor. If you are supplying a hazard ratio for a common outcome, set this to "hr"; if you are supplying an odds ratio for a common outcome, set this to "or"; if you are supplying a risk ratio or your outcome is rare, set this to "none" (default).

### Details

`tip_b()` is an alias for `tip_with_binary()`.

### Examples

```

## to estimate the relationship between an unmeasured confounder and outcome
## needed to tip analysis
tip_with_binary(1.2, exposed_confounder_prev = 0.5, unexposed_confounder_prev = 0)

## to estimate the number of unmeasured confounders specified needed to tip
## the analysis

```

```
tip_with_binary(1.2,
  exposed_confounder_prev = 0.5,
  unexposed_confounder_prev = 0,
  confounder_outcome_effect = 1.1)

## Example with broom
if (requireNamespace("broom", quietly = TRUE) &&
  requireNamespace("dplyr", quietly = TRUE)) {
  glm(am ~ mpg, data = mtcars, family = "binomial") %>%
  broom::tidy(conf.int = TRUE, exponentiate = TRUE) %>%
  dplyr::filter(term == "mpg") %>%
  dplyr::pull(conf.low) %>%
  tip_with_binary(exposed_confounder_prev = 1, confounder_outcome_effect = 1.15)
}
```

# Index

## \* datasets

exdata\_continuous, 12  
exdata\_rr, 12

adjust\_coef, 2  
adjust\_coef\_with\_binary, 3  
adjust\_coef\_with\_continuous  
(adjust\_coef), 2  
adjust\_coef\_with\_r2, 4  
adjust\_hr, 6  
adjust\_hr\_with\_binary, 7  
adjust\_hr\_with\_continuous (adjust\_hr), 6  
adjust\_or, 8  
adjust\_or\_with\_binary, 9  
adjust\_or\_with\_continuous (adjust\_or), 8  
adjust\_rr, 10  
adjust\_rr\_with\_binary, 11  
adjust\_rr\_with\_continuous (adjust\_rr),  
10

e\_value, 13  
exdata\_continuous, 12  
exdata\_rr, 12

observed\_bias\_order, 13  
observed\_bias\_tbl, 14  
observed\_bias\_tip, 15  
observed\_covariate\_e\_value, 16

r\_value, 16

sensemkr::adjusted\_estimate(), 4, 5, 22  
sensemkr::adjusted\_se(), 4  
sensemkr::robustness\_value(), 16, 17

tip, 17  
tip\_b (tip\_with\_binary), 29  
tip\_b(), 30  
tip\_c (tip), 17  
tip\_coef, 19  
tip\_coef\_with\_continuous (tip\_coef), 19

tip\_coef\_with\_r2, 21  
tip\_hr, 22  
tip\_hr\_with\_binary, 23  
tip\_hr\_with\_continuous (tip\_hr), 22  
tip\_or, 24  
tip\_or\_with\_binary, 26  
tip\_or\_with\_continuous (tip\_or), 24  
tip\_rr, 27  
tip\_rr\_with\_binary, 28  
tip\_rr\_with\_continuous (tip\_rr), 27  
tip\_with\_binary, 29  
tip\_with\_binary(), 30  
tip\_with\_continuous (tip), 17  
tipr, 19