

CurV_e – a L^AT_EX 2_ε class package for making Curriculum Vitae's. *

Didier Verna
mailto:didier@lrde.epita.fr
<http://www.lrde.epita.fr/~didier>

March 10, 2004

Abstract

CurV_e provides a L^AT_EX 2_ε class that hopefully will make your life easier when you want to write your CV. It provides you with a set of commands to create rubrics, entries in these rubrics etc. *CurV_e* will then properly format your CV for you (possibly splitting it onto multiple pages), which is usually the most painful part of CV writing. Another nice feature of *CurV_e* is its ability to manage different CV “flavors” simultaneously. It is in fact often the case that you want to maintain slightly divergent versions of your CV at the same time, in order to emphasize on different aspects of your background.

The *CurV_e* package is Copyright © 2000, 2001, 2002, 2003, 2004 Didier Verna, and distributed under the terms of the LPPL license.

1 Overview

The *CurV_e* package provides you with a document class for writing curriculum vitae's. The primary purpose of this package is to offer a set of predefined commands to specify the contents of your CV, while removing from you the burden of formatting it. This has two important consequence however: *CurV_e* will impose that you conform to its document structuring scheme, and will expect that you like the way it formats things :-). If you prefer another structure for your CV, or if you don't like the formatting (although it is highly configurable), then *CurV_e* is probably not for you.

Once you have installed *CurV_e*, you might want to start with processing the example file `cv.tex`. This will give you an idea of what a non customized CV looks like with *CurV_e*. You can also throw an eye to my own CV, which is written with *CurV_e* and has some more fancy hacking on top of it. It's in French, but only the appearance is important for you...My CV can be found at <http://www.lrde.epita.fr/~didier/perso/cv.php>.

1.1 Document Layout

A *CurV_e* CV begins with two optional headers (upper left and upper right) in which you usually put your name, address, email, whether you're married and so

*This document describes *CurV_e* v1.6, release date 2004/03/10.

on. These headers will respectively be left and right aligned. As of version 1.4, `CvV` lets you insert a small identity photo in the headers, either on the left, on the right, or between them. After these headers come an optional title and/or subtitle, which will be centered on the page.

1.1.1 Rubrics

The remaining of the document is composed of sections called “rubrics” in the `CvV` terminology. A rubric represents a major topic that you want to detail in your CV. Typical rubrics are “Education”, “Professional Experience” and the like. Rubrics have a title (centered by default) and appear under the form of properly aligned “entries” (see below). If a rubric has to be split across different pages, its title will be repeated automatically.

1.1.2 Entries

An entry is an item of information related to the rubric under which it appears. An entry has a “contents”, and an optional “key” under which it is classified. For instance, under the “Education” rubric, you could state that you got a Ph.D. in computer science in the year 2000. In that case, the year would be the entry’s key, and the “Ph.D. in computer science” part would be the entry’s contents. `CvV` aligns both keys and contents together. Keys are optional in order for you to classify several entries together (without repeating the same key over and over again).

1.1.3 Subrubrics

Additionally, you might want to further split your rubrics into “subrubrics”. For instance, in my own CV, I have a “Professional Experience” rubric, with three subrubrics: “Teaching”, “Research” and “Development”. This can be accomplished with a special command. Subrubrics are displayed in alignment with the entries’ contents by default, but are formatted differently so that they remain distinguishable.

1.2 Document Structure

1.2.1 Source File Splitting

`CvV` is based on the `LTXtable` package by David Carlisle. I won’t go into gory details, but this has an important implication: **each rubric must be in its own separate file**. In other words, your CV’s main source file is really a skeleton whose major task is to include the different rubrics from their respective source files.

This is not much of a hassle, really, and it actually made my life easier when I implemented the “flavor” mechanism described below.

1.2.2 The “flavor” Mechanism

It is often desirable to maintain several slightly divergent versions of one’s CV at the same time. For instance, when I was looking for a job some time ago, I had a version of my CV emphasizing on Artificial Intelligence, and another emphasizing

on Distributed Virtual Reality. Only the title and some entries in the “Professional Experience” rubric were a bit different; the main skeleton basically remained the same.

`CuVe` provides an easy-to-use mechanism for maintaining different “flavors” of your CV at the same time. You basically write different versions of (some of) your rubrics in different files, tell `CuVe` which flavor you want to format (`CuVe` can even ask you which one to use directly) and that’s it. `CuVe` will use the global skeleton, and whenever it finds a rubric file specialized for that particular flavor, it will use it. Otherwise, it will simply fall back to the default one (no particular flavor).

2 Using `CuVe`

First of all, please note that the `ltxtable` and `calc` packages are required because `CuVe` needs them. If you’re using the identity photo feature, the `graphicx` package is also required. You don’t have to load them explicitly though. As long as $\text{\LaTeX} 2_{\epsilon}$ can locate them, they will be used automatically.

2.1 Writing the Skeleton File

Say `\documentclass[options]{curve}` at the beginning of your skeleton file in order to use `CuVe`. The available options are described along the text, where appropriate.

2.1.1 Making Headers

`\lefthead` The `\lefthead` and `\righthead` macros take one mandatory argument which defines respectively the contents of the upper left and upper right headers. They can be used in the document’s preamble only. The headers will respectively be flushed to the left and to the right.

`\photo` If you want to insert a small identity photo into the header part, you can use the `\photo` macro (available since version 1.4). It takes a mandatory argument in which you pass the image file name, as you would to `\includegraphics`. This macro also takes an optional argument which lets you specify the horizontal position of the photo: the values can be `l` (the default), `c` or `r` meaning that the photo will appear on the left, center, or right.

`\photoscale` The headers’ horizontal layout is further controled by three additional macros. The `\photoscale` macro specifies the amount of text width that the photo should occupy. This should be a number between 0 and 1. By default, 0.1 is used (meaning 10% of `\textwidth`). The `\photosep` macro is a \LaTeX length that specifies the space to leave between the side of the photo and the next headers’s text. This is used only when the photo is on the left or right. By default, `10pt` is used. Finally, `\headerscale` specifies the proportion of the *remaining* space that the *left* textual header should occupy. It works like `\photoscale` and amounts to 0.5 by default.

Let me take an example to make this clearer. Suppose you have a `\photoscale` of 0.1 and a `\photosep` of `10pt`. The *remaining* space, that is, the space occupied by the textual headers, amounts to 90% of the text width, minus 10 points. If you then specify a `\headerscale` of 0.6, then the left header will take 60% of that remaining space, and the right one the other 40%.

`\headerspace` `\headerspace` is the amount of extra vertical space to put after the headers. This is a \LaTeX length that defaults to `10pt`.

`\makeheaders` If you have defined headers, make them appear by calling `\makeheaders` just after the beginning of your document. Note that calling this macro assumes that you have previously defined both headers (possibly empty, though). Otherwise, an error will be signaled. As of version 1.4, the `\makeheaders` command accepts an optional argument that controls the vertical alignment. When given, this argument must be either `t` (for top), `b` (for bottom) or `c` (for center; the default).

2.1.2 Making Titles

`\title` `\subtitle` The `\title` and `\subtitle` macros take one mandatory argument which define respectively your CV's title and subtitle. They can be used in the document's preamble only. These titles will be centered on the page.

`\titlespace` `\titlespace` is the amount of extra vertical space to put after the title(s). This is a \LaTeX length that defaults to `0pt`.

`\titlefont` `\subtitlefont` The `\titlefont` and `\subtitlefont` macros take one mandatory argument which redefine the fonts to use for the title and the subtitle. They can be used in the document's preamble only. By default, `\Huge\bfseries` and `\Huge\itshape` are used respectively.

`\maketitle` If you have defined a title (and possibly a subtitle), make it (them) appear by calling `\maketitle` after the beginning of your document, and just after `\makeheaders` if you happen use it. It is possible to omit the subtitle, but if you call `\maketitle` without having defined at least a title, an error will be signaled.

2.1.3 Choosing a Flavor

As you already know, each rubric must reside in its own separate file. For instance, if you have a "Professional Experience" rubric, you would write its contents into a file named `experience.tex`. The flavor mechanism works by assigning a pre-extension to rubric file names. For instance, suppose you want to make a special flavor of your CV emphasizing on "distributed virtual reality". You would call this flavor "dvr", and write the modified "Professional Experience" rubric into a file named `experience.dvr.tex`.

`\flavor` The `\flavor` macro takes one mandatory argument which specifies the flavor to use (in our example, `dvr`). Although this might be of little use, it is possible to change the flavor anywhere, even right in the middle of your CV's skeleton.

`ask` Instead of using the `\flavor` macro, you can make `CuVe` ask you at run-time which flavor to use by passing the `ask` option to it.

2.1.4 Including Rubrics

Apart from making headers and titles, the body of your skeleton file will usually contain nothing but directives to include the different rubrics of your CV.

`\makerubric` To include a rubric in your document, use `\makerubric`. This macro takes one mandatory argument which specifies the rubric to include at that point. The argument actually corresponds to the rubric file name **without any extension**. Continuing our previous example, you would say `\makerubric{experience}`. First, `CuVe` will try to find such a rubric file specific for the current flavor in use, (e.g.

`experience.dvr.tex`). If that fails, it will fall back to a non-flavored file (here, `experience.tex`). This allows you to specialize only the required rubrics and use the default ones otherwise.

2.2 Writing a Rubric File

2.2.1 The rubric Environment

<code>rubric</code>	The whole contents of a rubric file must be enclosed in a <code>rubric</code> environment. This environment takes one mandatory argument which specifies the rubric's title. When a rubric crosses several pages, its title is restated with a "continuation" text appended.
<code>\rubricalignment</code>	As of version 1.6, the rubric titles horizontal alignment can be changed thanks to the <code>\rubricalignment</code> macro. Possible values for its mandatory argument are <code>l</code> , <code>c</code> and <code>r</code> (meaning left, centered, or right relative to the whole text width), and <code>cl</code> and <code>cc</code> (meaning left or centered relative to the entries' contents). By default, rubric titles are centered (<code>c</code>).
<code>\rubricfont</code>	The <code>\rubricfont</code> macro takes one mandatory argument which redefines the font to use for rubric titles. By default, <code>\Large\bfseries</code> is used.
<code>\rubricspace</code>	<code>\rubricspace</code> is the amount of extra vertical space to put after the rubric title. This is a \LaTeX length that defaults to <code>10pt</code> .

2.2.2 Making Rubric Entries

<code>\entry</code>	You create entries in your rubrics by calling the <code>\entry</code> macro. The first (optional) argument specifies the key, and the second (mandatory) one specifies the contents. Both keys and contents are aligned within each rubric.
<code>\entry*</code>	Actually, the <code>\entry</code> macro was somewhat ill-designed at the first place. The <code>rubric</code> environment pretty much behaves as an <code>itemize</code> one, hence the idea of using an <code>\item</code> -like syntax. As of version 1.2, <code>CuVe</code> provides an <code>\entry*</code> macro which behaves like <code>\item</code> in lists: it takes the same first optional argument as the non starred version, but has no other argument. The entry's contents simply consists of the text following the macro call, up to the next <code>\entry</code> , <code>\entry*</code> or <code>\subrubric</code> (see below) call.
<code>\keyfont</code>	The <code>\keyfont</code> macro takes one mandatory argument which redefines the font to use for the entries' keys. By default, the standard document font is used.
<code>\prefix</code>	Each entry's contents can be prefixed with a visual clue (a symbol for instance). This comes in handy to make a clear distinction between different entries sharing the same key (which is not repeated). The <code>\prefix</code> macro takes one mandatory argument which redefines the prefix to use. By default, <code>\textbullet</code> is used.

2.2.3 Making Subrubrics

<code>\subrubric</code>	Within a single rubric, you can further separate entries into subrubrics. In order to do this, the <code>\subrubric</code> macro is provided. Its mandatory argument specifies the subrubric's title.
<code>\subrubricalignment</code>	As of version 1.6, the subrubrics horizontal alignment can be changed thanks to the <code>\subrubricalignment</code> macro. Possible values for its mandatory argument are <code>l</code> , <code>c</code> and <code>r</code> (meaning left, centered, or right relative to the whole text width), and <code>cl</code> and <code>cc</code> (meaning left or centered relative to the entries' contents). By default, subrubrics are left-aligned with the entries' contents (<code>cl</code>).

<code>\subrubricfont</code>	The <code>\subrubricfont</code> macro takes one mandatory argument which redefines the font to use for the subrubrics. By default, <code>\Large\itshape</code> is used.
<code>\subrubricspace</code>	<code>\subrubricspace</code> controls the amount of extra vertical space to put after subrubrics. This is a <code>L^AT_EX</code> length that defaults to <code>5pt</code> .
<code>\subrubricbeforespace</code>	<code>\subrubricbeforespace</code> controls the amount of extra vertical space to put <i>before</i> a subrubric when there are entries above. This is a <code>L^AT_EX</code> length that defaults to <code>10pt</code> .

2.3 Standard Class Features

2.3.1 Page Size and layout

<code>a4paper</code>	The <code>a4</code> , <code>a5</code> , <code>b4</code> , <code>letter</code> , <code>legal</code> and <code>executive</code> “paper” options allow you to select the type of page format you want. By default, <code>letterpaper</code> is used. The <code>landscape</code> options switches the horizontal and vertical settings. I’m not sure why I propose this option. Nobody wants to write a CV in landscape mode, right ?
<code>a5paper</code>	
<code>b4paper</code>	As of version 1.6, <code>C_uV_e</code> also supports the standard <code>oneside</code> and <code>twoside</code> class options. By default, <code>oneside</code> is used. In <code>twoside</code> mode, odd and even pages have a different geometry and headings layout.
<code>letterpaper</code>	
<code>legalpaper</code>	
<code>executivepaper</code>	
<code>landscape</code>	
<code>oneside</code>	
<code>twoside</code>	

2.3.2 Font Size

<code>10pt</code>	The <code>10pt</code> , <code>11pt</code> and <code>12pt</code> options let you choose the size of the default font you want to use. By default, <code>10pt</code> is used.
<code>11pt</code>	
<code>12pt</code>	

2.3.3 Output Mode

<code>final</code>	In <code>draft</code> mode, a black rule will be drawn at the end of overfull lines (as done by standard classes). Due to <code>C_uV_e</code> using the <code>L^AT_EX</code> package, a call to <code>\setlongtables</code> is performed in <code>final</code> mode. Please refer to the next section for more information on this. By default, <code>final</code> is used.
<code>draft</code>	

2.3.4 Page styles

As of version 1.6, `CuVe` supports the standard `LATEX` page style mechanism. Available styles are `empty`, `plain`, `headings` and `myheadings`. These styles have their usual meaning, given that rubric and subrubric names are used for marking purpose (the equivalent of chapters and sections in books for instance). By default, the page style is `empty`.

2.3.5 Bibliography

Most scientists include their own list of publications in their CV. The first thing you can do is create your own bibliography manually, and although this may appear boring, I actually encourage people to do so for at least three reasons (only my opinion of course):

- A CV should be strictly formatted and coherent in layout. Bibliography is no exception to this rule. In other words, it is prettier to have your publications formatted like the rest of your CV.
- Automatic bibliography generation tools produce references, which is silly in a CV because you don’t actually reference your papers anywhere (or do

you ?). So better to sort them another way, like, by year of publication as I do in my own CV.

- Manually adding, like, what ? Half a dozen papers a year in your CV is not that much of a burden after all.

Some people however have expressed the wish of having standard bibliography support in `CuVe`. Version 1.2 provides that. The standard `thebibliography` environment is now supported along with its `\bibitem` companion. The behavior is actually that of a `rubric` environment with its `\entry*` companion. This fact has two implications: firstly, the argument to the environment is unused in `CuVe` (but remains for compatibility with the rest of L^AT_EX) because `CuVe` itself formats the keys and contents properly aligned. Secondly, the bibliographic environment **must** reside in its own file, as any other rubric. Don't forget that if you happen to write the environment manually.

If you want to use BIB_TE_X, that's also possible of course. Do it as you would do in a random paper. You will probably issue a `\nocite{*}` command followed by a call to `\bibliography`. In `CuVe`, this uses the `bb1` file as a rubric one.

2.3.6 Internationalization

`CuVe` currently supports English, French, Spanish, Italian, German, Danish, Dutch and Portuguese. You can select the language you want to use by using the corresponding option. The `french` and `francais` options are synonyms. The `german` and `ngerman` options are currently equivalent. So are the `portuges`, `portuguese`, `german`, `ngerman`, `brazil` and `brazilian` options.

If you want a finer grain on the language-dependent parts of `CuVe`, the following macros are provided.

The `\continuedname` macro takes one mandatory argument which redefines the continuation text output when rubrics extend across several pages. By default, “*space*(continued)” is used in English. Although this might be of little use, it is possible to change the continuation text in the middle of your document, provided that you do so outside the `rubric` environment.

The `\listpubname` macro takes one mandatory argument which redefines the title of the bibliographic section (when you use the provided bibliography support). By default, “List of Publications” is used in English.

3 Hints, Tricks, Tips

Here are some tips that I use for my own CV. You might find them of some interest.

3.1 Page Geometry

First of all, it is common to have very thin margins in curriculum vitae's. `CuVe` does not do anything special about this because I don't think that belongs to its duty. The `geometry` package comes in handy if you want to reduce your margins.

3.2 The ltx Extension

Personally, I prefer to keep `.tex` for \TeX files, and use the `ltx` extension for \LaTeX . This is supported by `CuVe` which will actually prefer `ltx` files over `tex` ones, especially when including rubrics. To be more precise, suppose you are building a flavor `flv` of your CV. A call to `\makerubric{foo}` will try to use the following files in that order:

```
foo.flv.ltx
foo.flv.tex
foo.ltx
foo.tex
```

3.3 Longtables

The `LTXtable` package on which `CuVe` is based is a mix of `tabularx` and `longtables`. If you read the documentation of the later, you will discover that for table width computing reasons (especially when a table crosses several pages), \LaTeX has to be called twice, sometimes three times, with the last run involving a call to `\setlongtables`.

Normally, you shouldn't have problems with `CuVe` because all tables are set to the maximum width. However, for safety reasons (I mean, just to be sure...), `CuVe` automatically calls `\setlongtables` in `final` mode. If you experiment problems with the formatting, you should process your document once or twice in `draft` mode, and a second or third time in `final` mode.

Ah, and also, since you're basically working in tabular environments, don't forget that you are not allowed to use the `\` command...

3.4 Managing Different Flavors

If you maintain different flavors of your CV at the same time, you probably want to rebuild all of them after any modification. Since you have a single skeleton file for all of them (say, `cv.tex`), the output file will have the same name for all flavors (say, `cv.dvi`). This can bother you if you want all flavors of your formatted CV available at the same time.

To remedy this problem, I usually use the `ask` option and a makefile to build the different flavors and move the output file to flavor-specific name. Here is a typical makefile target that should clarify (or maybe darken ?) what I am saying:

```
cv.$(FLAVOR).dvi: cv.ltx $(RUBRICS)
    echo $(FLAVOR) | latex cv.ltx
    mv cv.dvi $@
```

As you can see, the shell is responsible for answering the question.

3.5 More On Flavors

In order to implement the flavor mechanism, the \LaTeX macro `\input` has been redefined to look for "flavored" files first. This is actually very nice because you can use it if you want to make different flavors of text that does not belong in rubrics.

For instance, suppose you want a special version of the subtitle of your CV for the flavor `flv`. Create a file called `subtitle.flv.ltx` and put something like “`\subtitle{special subtitle}`” in it. Do something similar for the default subtitle. Now go to the skeleton of your CV, and write `\input{subtitle}` in the preamble. That’s it. You’ll have different subtitles in your different CV flavors.

4 AUC- \TeX support

AUC- \TeX is a powerful major mode for editing \TeX documents in Emacs or XEmacs. In particular, it provides automatic completion of macro names once they are known. *Curve* supports AUC- \TeX by providing a style file named `curve.el` which contains AUC- \TeX definitions for the relevant macros. This file should be installed to a location where AUC- \TeX can find it (usually in a subdirectory of your \LaTeX styles directory). Please refer to the AUC- \TeX documentation for more information on this.

As of version 1.2, *Curve* has an improved AUC- \TeX support. Most notably, the command `M-RET` will insert an `\entry*` macro within a `rubric` environment. Also, the `\makerubric` macro handling now removes both the file extension and the file flavor extension.

5 Changes

- v1.6 Support for rubric and subrubric titles horizontal alignment
 Support for standard \LaTeX page style mechanism
 Support for `oneside` and `twoside` options
 Support for Portuguese thanks to Adiel Mittmann <adiel@inf.ufsc.br>
 Bug fix in `\bibliography`: protect against non existant files, spotted thanks to Andrew Comport <Andrew.Comport@irisa.fr>
 Fix conflict with `hyperref` in some bibliography definitions
- v1.5 Support for Dutch thanks to Thomas Delaet
 <Thomas.Delaet@student.kuleuven.ac.be>
 Typo fix in rubric environment, spotted by Torsten Liesk
 <torsten.liesk@gmx.net>
- v1.4 Support for photo inclusion
 Support for headers horizontal scaling
 Optional argument to `\makeheaders` for vertical alignment, suggested by Dan Luecking <luecking@uark.edu>
- v1.3 Support for Danish thanks to Kim Rud Bille <krbi01@control.auc.dk>
- v1.2 Support for standard bibliography mechanism(s)
 New macro `\entry*`
 Improvements in AUC- \TeX support
 Support for German thanks to Harald Harders <h.harders@tu-bs.de>
 Support for Spanish thanks to Agustín Martín <agusmb@netscape.net>
- v1.1 Support for Italian thanks to Riccardo Murri <murri@phc.unipi.it>

6 The Code

```
1 \NeedsTeXFormat{LaTeX2e}
2 \ProvidesClass{curve}[2004/03/10 v1.6
3           Curriculum Vitae class for LaTeX2e]
4
5 \RequirePackage{ltxtable}
6 \RequirePackage{calc}
7
```

The following macro tests strings equality. It avoids the hassle of this stupid T_EX scheme that prevents simple conditionals imbrication.

```
8 \newif\ifstrok\strokfalse
9 \def\strtest#1#2{%
10  \def\@strone{#1}\def\@strtwo{#2}%
11  \ifstrok\else\ifx\@strone\@strtwo\stroktrue\fi\fi}
12
```

6.1 The Rubric File

We don't want to output an extra `subrubricbeforespace` if no entry is present before the subrubric. This is done by using an `\@beforespace` command which is set to `0pt` at the beginning of each rubric, and switched to the proper value when an entry is added.

The `@nextentry` command is used to implement `\entry*` while maintaining backward compatibility with `\entry` and `\subrubric`. A new entry or a subrubric might have to close the preceding entry if it was opened using the starred form.

```
13 \gdef\@nextentry{}
14
```

6.1.1 Entries

```
\keyfont
\prefix 15 \def\@keyfont{}
\entry  16 \newcommand\keyfont[1]{\gdef\@keyfont{#1}}
17
18 \def\@prefix{\textbullet}
19 \newcommand\prefix[1]{\gdef\@prefix{#1}}
20
21 \newcommand\@entry[2] [] {%
22  \@nextentry
23  \gdef\@nextentry{}%
24  \gdef\@beforespace{-\subrubricbeforespace}%
25  #1&\@prefix&#2\\}
26
27 \newcommand\@sentry[1] [] {%
28  \@nextentry
29  \gdef\@nextentry{\}%
30  \gdef\@beforespace{-\subrubricbeforespace}%
31  #1&\@prefix&}
32
33 \newcommand\entry{\@ifstar{\@sentry}{\@entry}}
34
```

6.1.2 Subrubrics

```
\subrubricfont
\subrubricbeforespace 35 \def\@subrubricfont{\Large\itshape}
\subrubricspace 36 \newcommand\subrubricfont[1]{\gdef\@subrubricfont{#1}}
\subrubricalignment 37
\subrubric 38 \newlength\subrubricbeforespace
39 \setlength\subrubricbeforespace{10pt}
40
41 \newlength\subrubricspace
42 \setlength\subrubricspace{5pt}
43
44 \let\@subrubricmark\@gobble
45
```

Note that `\@subrubricmark` is called outside the raisebox. That's because otherwise, the mark would not go to the toplevel page vertical box, and T_EX would not notice it.

```
46 \def\@@subrubric#1{%
47   \raisebox{\@beforespace}{\@subrubricfont#1}%
48   \@subrubricmark{#1}%
49   \par\vspace\subrubricspace}
50
51 \def\@subrubric@l#1{\multicolumn{3}{@{}l}{\@@subrubric{#1}}}
52 \def\@subrubric@c#1{\multicolumn{3}{@{}c}{\@@subrubric{#1}}}
53 \def\@subrubric@r#1{\multicolumn{3}{@{}r}{\@@subrubric{#1}}}
54 \def\@subrubric@cl#1&\multicolumn{2}{l}{\@@subrubric{#1}}
55 \def\@subrubric@cc#1&\multicolumn{2}{c}{\@@subrubric{#1}}
56
57 \let\@subrubric\@subrubric@cl
58
59 \newcommand\subrubricalignment[1]{%
60   \def\@curve@temp@a{\let\@subrubric
61     \expandafter\@curve@temp@a\csname @subrubric@#1\endcsname
62     \@ifundefined{subrubric}{%
63       \ClassError{curve}{Invalid subrubric alignment}{%
64         You have called \protect\subrubricalignment\space with an invalid value.%
65         \MessageBreak
66         Valid options include l, c, r, cl and cc.\MessageBreak
67         Type X <return> to quit, fix the typo, and rerun LaTeX.}}
68 }
69
70 \newcommand\subrubric[1]{%
71   \@nextentry
72   \noalign{\gdef\@nextentry{}}%
73   \@subrubric{#1}\}
74
```

6.1.3 Rubrics

The `\@almosttextwidth` length remains only for backward compatibility. It is not used anymore.

```
\rubricfont
\rubricspace 75 \newlength{\@almosttextwidth}
\rubricalignment 76 \AtBeginDocument{\setlength\@almosttextwidth{\textwidth-\hfuzz}}
\continuedname
rubric
```

```

77
78 \def\@rubricfont{\Large\bfseries}
79 \newcommand\rubricfont[1]{\gdef\@rubricfont{#1}}
80
81 \newlength\rubricspace
82 \setlength\rubricspace{10pt}
83
84 \let\@rubricmark\@gobble
85
86 \def\@@rubrichead#1{\@rubricfont#1\par\vspace\rubricspace}
87
88 \def\@rubrichead@l#1{\multicolumn{3}{@{}l}{\@@rubrichead{#1}}\}
89 \def\@rubrichead@c#1{\multicolumn{3}{@{}c}{\@@rubrichead{#1}}\}
90 \def\@rubrichead@r#1{\multicolumn{3}{@{}r}{\@@rubrichead{#1}}\}
91 \def\@rubrichead@cl#1{\multicolumn{2}{l}{\@@rubrichead{#1}}\}
92 \def\@rubrichead@cc#1{\multicolumn{2}{c}{\@@rubrichead{#1}}\}
93
94 \let\@rubrichead\@rubrichead@c
95
96 \newcommand\rubricalignment[1]{%
97   \def\@curve@temp@a{\let\@rubrichead}
98   \expandafter\@curve@temp@a\csname @rubrichead@#1\endcsname
99   \ifundefined{\@rubrichead}{%
100     \ClassError{curve}{Invalid rubric alignment}{%
101       You have called \protect\rubricalignment\space with an invalid value.%
102       \MessageBreak
103       Valid options include l, c, r, cl and cc.\MessageBreak
104       Type X <return> to quit, fix the typo, and rerun LaTeX.}}
105 }
106
107 \newcommand\continuedname[1]{\gdef\@continuedname{#1}}
108
109 \newenvironment{rubric}[1]{%
110   %% \begin{rubric}
111   \gdef\@beforespace{0pt}%
112   \gdef\@nextentry{}%
113   \begin{longtable}{@{}>{\@keyfont}ll@{~}X}
114     \@rubrichead{#1}
115     \endfirsthead
116     \@rubrichead{#1}\@continuedname}
117     \endhead
118     \noalign{\@rubricmark{#1}}}%
119   %% \end{rubric}
120   \@nextentry
121   \end{longtable}}
122

```

Marking commands don't seem to work in longtable headings. So the rubric mark is issued just after it.

6.2 The Skeleton File

6.2.1 Headers

\photoscale Here are some scales and lengths used to format the headers:
\photosep
\headerscale
\headerspace

```

123 \newlength\photo@width
124 \newlength\lefthead@width
125 \newlength\righthead@width
126
127 \def\photo@scale{.1}
128 \newcommand\photoscale[1]{\gdef\photo@scale{#1}}
129 \@onlypreamble\photoscale
130
131 \newlength\photosep
132 \setlength\photosep{10pt}
133
134 \def\header@scale{.5}
135 \newcommand\headerscale[1]{\gdef\header@scale{#1}}
136 \@onlypreamble\headerscale
137
138 \newlength\headerspace
139 \setlength\headerspace{10pt}
140

```

If the user calls `\makeheaders` without specifying headers first, an error will be generated. The same applies for the title (not the subtitle), but this is already managed by L^AT_EX itself.

```

\lefthead 141 \def\@lefthead{%
\righthead 142 \ClassError{curve}{No \protect\lefthead\space given}{%
143   You have called \protect\makeheaders, %
144   but you didn't provide a left header.\MessageBreak
145   Type X <return> to quit, add a call to \protect\lefthead\space %
146   in the preamble of your CV,\MessageBreak
147   and rerun LaTeX.}}
148 \newcommand\lefthead[1]{\gdef\@lefthead{#1}}
149 \@onlypreamble\lefthead
150
151 \def\@righthead{%
152 \ClassError{curve}{No \protect\righthead\space given}{%
153   You have called \protect\makeheaders, %
154   but you didn't provide a right header.\MessageBreak
155   Type X <return> to quit, add a call to \protect\righthead\space %
156   in the preamble of your CV,\MessageBreak
157   and rerun LaTeX.}}
158 \newcommand\righthead[1]{\gdef\@righthead{#1}}
159 \@onlypreamble\righthead
160

```

These different versions of the photo inclusion command exist for proper alignment of the picture itself with the left and right headers.

```

161 \def\includephoto@t{%
162   \raisebox{.7\baselineskip-\height}{%
163     \includegraphics[width=\photo@width]{\photo@file}}
164
165 \def\includephoto@c{%
166   \raisebox{-.5\height}{%
167     \includegraphics[width=\photo@width]{\photo@file}}
168
169 \def\includephoto@b{\includegraphics[width=\photo@width]{\photo@file}}
170

```

And here are the different versions of the `\makeheaders` command:

```

171 \def\makeheaders@l#1{%
172   \setlength\photo@width{\photo@scale\textwidth}
173   \setlength\lefthead@width{%
174     (\textwidth - \photo@width - \photosep) * \real{\header@scale}}
175   \setlength\righthead@width{%
176     \textwidth - \photo@width - \photosep - \lefthead@width}
177   \parbox[#1]{\photo@width + \photosep}{\includephoto@hspace\photosep}%
178   \parbox[#1]{\lefthead@width}{\@lefthead}%
179   \parbox[#1]{\righthead@width}{\raggedleft\@righthead}}
180
181 \def\makeheaders@c#1{%
182   \setlength\photo@width{\photo@scale\textwidth}
183   \setlength\lefthead@width{(\textwidth - \photo@width) * \real{.5}}
184   \setlength\righthead@width{\lefthead@width}
185   \parbox[#1]{\lefthead@width}{\@lefthead}%
186   \parbox[#1]{\photo@width}{\includephoto@}%
187   \parbox[#1]{\righthead@width}{\raggedleft\@righthead}}
188
189 \def\makeheaders@r#1{%
190   \setlength\photo@width{\photo@scale\textwidth}
191   \setlength\lefthead@width{%
192     (\textwidth - \photo@width - \photosep) * \real{\header@scale}}
193   \setlength\righthead@width{%
194     \textwidth - \photo@width - \photosep - \lefthead@width}
195   \parbox[#1]{\lefthead@width}{\@lefthead}%
196   \parbox[#1]{\righthead@width}{\raggedleft\@righthead}%
197   \parbox[#1]{\photo@width + \photosep}{\hspace\photosep\includephoto@}}
198
199 \def\makeheaders@#1{%
200   \setlength\lefthead@width{\header@scale\textwidth}%
201   \setlength\righthead@width{\textwidth - \lefthead@width}%
202   \parbox[#1]{\lefthead@width}{\@lefthead}%
203   \parbox[#1]{\righthead@width}{\raggedleft\@righthead}}
204

```

`\photo`

```

205 \newcommand\photo[2][l]{%
206   \RequirePackage{graphicx}
207   \strokfalse\strtest{#1}{l}\strtest{#1}{r}\strtest{#1}{c}%
208   \ifstrok\else\ClassError{curve}{Invalid argument to \protect\photo}{%
209     Argument 2 of \protect\photo must be 'l', 'r' or 'c'.}\fi
210   \def\tmp@cmd{\global\let\makeheaders@}
211   \expandafter\tmp@cmd\csname makeheaders@#1\endcsname
212   \gdef\photo@file{#2}}
213 \@onlypreamble\photo
214

```

`\makeheaders`

```

215 \newcommand\makeheaders[1][c]{%
216   \strokfalse\strtest{#1}{t}\strtest{#1}{b}\strtest{#1}{c}%
217   \ifstrok\else\ClassError{curve}{Invalid argument to \protect\makeheaders}{%
218     Argument of \protect\makeheaders must be 't', 'b' or 'c'.}\fi
219   \def\tmp@cmd{\global\let\includephoto@}
220   \expandafter\tmp@cmd\csname includephoto@#1\endcsname

```

```

221 \makeheaders@{#1}%
222 \par\vspace\headerspace}
223

```

6.2.2 Titles

```

\titelfont
\subtitle 224 \def\@titelfont{\Huge\bfseries}
\subtitelfont 225 \newcommand\titelfont[1]{\gdef\@titelfont{#1}}
\titlespace 226 \@onlypreamble\titelfont
\maketitle 227
228 \@onlypreamble\title
229
230 \let\@subtitle\@undefined
231 \newcommand\subtitle[1]{\gdef\@subtitle{#1}}
232 \@onlypreamble\subtitle
233
234 \def\@subtitelfont{\huge\itshape}
235 \newcommand\subtitelfont[1]{\gdef\@subtitelfont{#1}}
236 \@onlypreamble\subtitelfont
237
238 \newlength\titlespace
239 \setlength\titlespace{0pt}
240
241 \newcommand\maketitle{%
242 \begin{center}
243 {\@titelfont\@title}
244 \ifx\@subtitle\@undefined\else\\ \@subtitelfont\@subtitle\fi
245 \end{center}
246 \vspace\titlespace}
247

```

6.2.3 Rubric Inclusion

```

\input
\makerubric 248 \let\@flavor\empty
249 \newcommand\flavor[1]{\gdef\@flavor{#1}
250 \ifx\@flavor\empty\else\edef\@flavor{.\@flavor}\fi}
251
252 \DeclareOption{ask}{%
253 \typein[\@flavor]{Please specify a CV flavor (none by default):}
254 \ifx\@flavor\empty\else\edef\@flavor{.\@flavor}\fi}
255
256 \def\@curveinput#1{%
257 \IfFileExists{#1\@flavor.ltx}{\@input{#1\@flavor.ltx}}{%
258 \IfFileExists{#1\@flavor.tex}{\@input{#1\@flavor.tex}}{%
259 \IfFileExists{#1.ltx}{\@input{#1.ltx}}{%
260 \IfFileExists{#1.tex}{\@input{#1.tex}}{%
261 \@input{#1}}}}}}
262 \renewcommand\input{\@ifnextchar\bgroup\@curveinput\@input}
263
264 \newcommand\makerubric[1]{\LTXtable{\@almosttextwidth}{#1}}
265

```

6.2.4 Bibliography

`\listpubname`

```
266 \let\newblock\par
267 \newcounter{bibcount}
268
The internal bibitem macro definitions are postponed until the beginning of the
document because hyperref redefines them. So we have to override these new
definitions yet again.
269 \AtBeginDocument{
270 \def\@bibitem[#1]#2{\entry*[\@biblabel{#1}]%
271 \if@filesw{%
272 \let\protect\noexpand%
273 \immediate\write\@auxout{\string\bibcite{#2}{#1}}%
274 \fi%
275 \ignorespaces}
276 \def\@bibitem#1{\entry*[\stepcounter{bibcount}\@biblabel{\thebibcount}]%
277 \if@filesw%
278 \immediate\write\@auxout{\string\bibcite{#1}{\thebibcount}}%
279 \fi%
280 \ignorespaces}
281 }
282
283 \def\bibliography#1{%
284 \if@filesw
285 \immediate\write\@auxout{\string\bibdata{#1}}%
286 \fi
287 \IfFileExists{\jobname.bbl}{\makerubric{\jobname.bbl}}{%
288 \typeout{No file \jobname.bbl.}}%
289
290 \newcommand\listpubname[1]{\gdef\@listpubname{#1}}
291 \newenvironment{thebibliography}[1]{%
292 \begin{rubric}{\@listpubname}
293 }{%
294 \end{rubric}
295 }
296
```

6.3 Language Processing

```
297 \DeclareOption{english}{%
298 \continuedname{~(continued)}}
299 \listpubname{List of Publications}}
300 \DeclareOption{french}{%
301 \continuedname{~(suite)}}
302 \listpubname{Liste des Publications}}
303 \DeclareOption{francais}{%
304 \ExecuteOptions{french}}
305 \DeclareOption{spanish}{%
306 \continuedname{~(contin'ua)}}
307 \listpubname{Lista de Publicaciones}}
308 \DeclareOption{italian}{%
309 \continuedname{~(continua)}}

```

```

310 \listpubname{Publicazioni}}
311 \DeclareOption{german}{%
312 \continuedname{~(fortgesetzt)}
313 \listpubname{Verzeichnis der Ver\ "offentlichungen}}
314 \DeclareOption{ngerman}{%
315 \ExecuteOptions{german}}
316 \DeclareOption{danish}{%
317 \continuedname{~(forsat)}
318 \listpubname{Udgivelser}}
319 \DeclareOption{dutch}{%
320 \continuedname{~(vervolg)}
321 \listpubname{Publicaties}}
322 \DeclareOption{portuges}{%
323 \continuedname{~(continua\c c\~ao)}
324 \listpubname{Publica\c c\~oes}}
325 \DeclareOption{portuguese}{%
326 \ExecuteOptions{portuges}}
327 \DeclareOption{brazil}{%
328 \ExecuteOptions{portuges}}
329 \DeclareOption{brazilian}{%
330 \ExecuteOptions{portuges}}
331

```

6.4 Standard Class Processing

```

332 \DeclareOption{a4paper}{
333 \setlength\paperheight{297mm}
334 \setlength\paperwidth{210mm}}
335 \DeclareOption{a5paper}{
336 \setlength\paperheight{210mm}
337 \setlength\paperwidth{148mm}}
338 \DeclareOption{b5paper}{
339 \setlength\paperheight{250mm}
340 \setlength\paperwidth{176mm}}
341 \DeclareOption{letterpaper}{
342 \setlength\paperheight{11in}
343 \setlength\paperwidth{8.5in}}
344 \DeclareOption{legalpaper}{
345 \setlength\paperheight{14in}
346 \setlength\paperwidth{8.5in}}
347 \DeclareOption{executivepaper}{
348 \setlength\paperheight{10.5in}
349 \setlength\paperwidth{7.25in}}
350 \DeclareOption{landscape}{
351 \setlength\@tempdima{\paperheight}
352 \setlength\paperheight{\paperwidth}
353 \setlength\paperwidth{\@tempdima}}
354
355 \DeclareOption{10pt}{\def\@ptsize{0}}
356 \DeclareOption{11pt}{\def\@ptsize{1}}
357 \DeclareOption{12pt}{\def\@ptsize{2}}
358
359 \DeclareOption{oneside}{\@twosidefalse\@mparswitchfalse}
360 \DeclareOption{twoside}{\@twosidetrue\@mparswitchtrue}
361

```

```

362 \DeclareOption{draft}{\setlength\overfullrule{5pt}}
363 \DeclareOption{final}{%
364   \setlength\overfullrule{0pt}
365   \setlongtables}
366
367 \ExecuteOptions{english,letterpaper,10pt,oneside,final}
368 \ProcessOptions
369
370 \input{size1\@ptsize.clo}
371 \setlength\parindent{0pt}
372 \setlength\parskip{0pt}
373 \setlength\tabcolsep{10pt}
374 \setlength\arrayrulewidth{.4\p@}
375 \raggedbottom
376 \onecolumn
377 \pagestyle{empty}
378 \pagenumbering{arabic}
379
380 \if@twoside
381   \def\ps@headings{%
382     \let\@oddfoot\@empty\let\@evenfoot\@empty
383     \def\@evenhead{\thepage\hfil\slshape\leftmark}%
384     \def\@oddhead{\slshape\rightmark}\hfil\thepage}%
385     \let\@mkboth\markboth
386     \def\@rubricmark##1{\markboth{\MakeUppercase{##1}}-}%
387     \def\@subrubricmark##1{\markright{##1}}%
388   }
389 \else
390   \def\ps@headings{%
391     \let\@oddfoot\@empty
392     \def\@oddhead{\slshape\rightmark}\hfil\thepage}%
393     \let\@mkboth\markboth
394     \def\@rubricmark##1{\markright{\MakeUppercase{##1}}}%
395   }
396 \fi
397 \def\ps@myheadings{%
398   \let\@oddfoot\@empty\let\@evenfoot\@empty
399   \def\@evenhead{\thepage\hfil\slshape\leftmark}%
400   \def\@oddhead{\slshape\rightmark}\hfil\thepage}%
401   \let\@mkboth\@gobbletwo
402   \let\@rubricmark\@gobble
403   \let\@subrubricmark\@gobble
404 }
405

```

Well, I think that's it. Enjoy using *Cu^{re}V_e*!